



LightGuard® 350XL Sealed Fiber Optic Splice Closure

The LightGuard (LG) 350XL is a sealed dome closure designed for large count fiber splicing (up to 864 single or 2592 mass) in a butt configuration. Utilized in aerial or underground environments where a sealed closure is required, the LG-350XL is ideal for high fiber count splicing and requires only a common can wrench for installation. A Phillips head screw is used to secure the tray support to the basket.

Features

- Supports stranded loose tube or ribbon fiber cables in either armored or dielectric configurations
- Installation and re-entry requires only a common can wrench
- Fully sealed to protect fiber and splices ensuring longevity
- Fully kitted with all parts to install five cables
- Accommodates up to 7 cables
- Oversized basket allows multiple configurations of slack storage
- O-Ring and Locking Ring for increased protection

Specifications

PARAMETER	VALUE	
Splice Capacity (Max.)—Single, Mass, Mechanical	864, 2592, 288	
Number of Splice Trays (Max.)—Single, Mass, Mechanical*	9, 9, 9	
Cable Entrance Configuration	Butt	
Cables	5 to 7	
Cable Sizes (Min. O.D Max. O.D.) Included Grommets Single in. (mm) Additional Grommets	(2) Express Ports 0.40" - 1.18" (10.0 - 30.0) 0.38" - 0.56"	(3) Drop Ports 0.30" - 1.08" (7.6 - 27.4)
Dual Exp. Port Only in. (mm)	(9.7 - 14.2)	
Dimensions - (L x D) in. (mm)	31.0" x 12.00" (788.5 x 305.0)	
Weight - lbs. (kg)	25.0 (11.3)	



LightGuard® 350XL Sealed Fiber Optic Splice Closure

Ordering Information

DESCRIPTION	AFL NO.
LG-350XL-U-0 Fiber Optic Splice Closure — Stores 864 single fusion or 2592 mass fusion, includes (5) cable kits for sealing/retention and (2) ground terminals with removable bond. Not included: Splice Trays, Cable Grounding Kits or Hanger Brackets	
LL-4896 Universal Splice Tray — Stores (96) single fusion splices or (24) mass fusion splices (288 F), *Mechanical. Max. of 9 trays in the LG-350XL	
LL-4896-R Mass Splice Tray — Stores (24) mass fusion splices (288 F). Max. of 9 trays in the LG-350XL	
LL-4896-L Single Splice Tray – Stores (96) single fusion splices. Max. of 9 trays in the LG-350XL	
LG-350XL Single Grommet Kit (Min. 0.40" - Max. 1.18") — For use in LG-350XL on Express Port side	
LG-350XL Dual Grommet Kit (Min. 0.38" - Max. 0.56") — For use in LG-350XL on Express Port side	
LG-350XL Single Grommet Kit (Min. 0.30" - Max. 1.08") — For use in LG-350XL on Drop Port side	
LG-350XL Drop 4 Flat Drop Grommet Kit – For use with standard flat drop cable and round cable up to 0.25" O.D.	
Strand Mount Hanger Bracket – For use with LG-350XL in strand or vault mounting	
1x6 Fiber Router Kit with furcation tubes	
CGK-5 Cable Grounding Kit (pack of 5) — Clamp-On Ground Cable Only	
*Mechanical Splice Kit. Includes 10 pieces of VHB tape. Used in all splice trays. Each piece holds 12 splices.	
O-Ring and Lock Ring Kit — For use with LG-350XL	
Transition tubing 16.25" long — Used to transport ribbon to the splice trays. (20) per kit	

^{*} See LL-4896 Splice Tray Specifications.

Qualifications

GOVERNING BODY	STANDARD CODE	
Telcordia	GR-771	
Rural Utilities Service (RUS)	Listed	

Contact AFL for further details.