

## OFI-200 Optical Fiber Identifier



### Features

- 5-year product warranty; 3-year recommended calibration interval
- Rugged, hand-held, lightweight, and easy-to-use
- Unique optical head with two-position plunger for use with all fiber types
- Visually and audibly indicates tone signal across 2 kHz range

### Applications

- Live fiber identification to avoid technician-induced service outages
- Fiber tracing or identification with CW or test tones
- Testing 250  $\mu\text{m}$ , 900  $\mu\text{m}$  coated, 2 mm, 3 mm jacketed, and ribbon fiber

AFL Optical Fiber Identifiers are rugged, hand-held, and easy-to-use fiber optic test instruments designed to detect optical signals transmitted through a single-mode fiber without disrupting traffic.

The OFI-200 is simply clamped onto a fiber and indicates if there is NO SIGNAL, TONE, or TRAFFIC and the associated signal direction. This permits network personnel to easily and quickly identify a specific fiber without the risk of disrupting service. When testing coated fibers, the slim design of the OFI-200 allows easier access on a splice tray where the amount of workspace is limited.

**No adapters to purchase, store, swap, or misplace:** The OFI-200 uses a unique optical head design featuring a two-position plunger that enables it to be used with 250  $\mu\text{m}$ , 900  $\mu\text{m}$ , and ribbon fiber or 2 mm and 3 mm jacketed fiber. Other brands of optical fiber identifiers require users to purchase, store, and change optical plungers each time a different type of fiber is tested.

**Low insertion loss for in-service ID tasks:** The OFI-200 optical head induces a safe, repeatable macro-bend to the fiber that allows a small amount of light to escape for analysis. The insertion loss induced by the macro-bend is too small to affect the signal on the fiber and the integrity of the fiber is unaffected by the measurement process.

**Designed for the real world:** The OFI-200 is a simple, easy-to-use tool that features rugged, drop-proof construction perfect for inside or outside plant use. Its ergonomically designed macro-bend trigger is comfortable to use and the integrated, backlit LCD display enables it to be used in dimly lit spaces. The OFI-200 uses readily available 1.5 V AAA batteries, which power thousands of fiber tests before needing to be replaced.

# OFI-200 Optical Fiber Identifier

## Specifications <sup>a</sup>

DETECTABLE SIGNAL RANGE			
FIBER TYPE <sup>b</sup>	PARAMETER	TEST CONDITIONS <sup>c</sup>	OFI-200D
250 µm coated fiber (SMF-28 with 250 µm CPC6 coating)	Minimum level detected, average power	1310 nm, CW or Traffic 1310 nm, Tone 1550 nm, CW or Traffic 1550 nm, Tone	-40 dBm -43 dBm -45 dBm -50 dBm
	Insertion loss (typical)	1310 nm 1550 nm	0.6 dB 2.5 dB
3 mm jacketed fiber (SMF-28 with 250 µm CPC6 coating and 3 mm, yellow jacket)	Minimum level detected, average power	1310 nm, CW or Traffic 1310 nm, Tone 1550 nm, CW or Traffic 1550 nm, Tone	-30 dBm -32 dBm -33 dBm -37 dBm
	Insertion loss (typical)	1310 nm 1550 nm	0.8 dB 2.5 dB
OPTICAL SPECIFICATIONS <sup>d</sup>			
Detector Type	InGaAs		
Wavelength Range	800 - 1700 nm		
Calibrated Size of Fiber and Wavelength	N/A		
Fiber Stress	<100 kPSI max		
Fiber Size	250 µm, 900 µm, ribbon, 2 mm or 3 mm and jacketed fiber		
Tone Detection	2000 ± 100 Hz		
GENERAL SPECIFICATIONS			
Display Type	N/A		
Power	1 9-Volt Alkaline		
Battery Life	>10,000 operations typical		
Operation Temperature	0°C to 50°C 90 % RH (Non-condensing)		
Storage Temperature	-30°C to +60°C 90 % RH (Non-condensing)		
Dimensions (H x W x D)	22 x 3.8 x 2.8 cm (8.5 x 1.5 x 1.1 in)		
Weight	210 g (7.5 oz)		

### Notes:


- a. All specifications stated above are as measured at 25°C.
- b. 250 µm coated fiber parameters are specified with OFI plunger in the "250/900/RIB" position. 2 mm/ 3 mm jacketed fiber parameters are specified with OFI plunger in the "2 mm/3 mm" position.
- c. CW is a light signal that is not modulated. Traffic is a light signal modulated by a random data sequence. Tone is a light signal modulated into a nominal 50% duty cycle square wave.
- d. Unless noted otherwise, all specifications are typical. Actual results can vary by several dB depending on fiber type, coating material, jacket color, jacket hardness, and other factors.

# OFI-200 Optical Fiber Identifier

## Ordering Information

INCLUDES	AFL NO.
Users guide and carry case	OFI-200D

## Recommended Products



**FlexScan® FS300 (quad) and FS200 (single-mode) OTRDs**

- SmartAuto® 1-button automated testing for fast results
- LinkMap® color-coded icons for easy troubleshooting
- FleXpress® mode (FS200) completes OTDR test in <5 seconds!
- Integrated Source, Power Meter and VFL



**Optical Light Sources**

- Encircled Flux Compliant
- 5-Year Product Warranty
- Integrated LED and Laser light sources

## Qualifications

CATEGORY	REGULATION/STANDARD	QUALIFICATION
CE Marking	EU	Compliant to relevant EU Directives on health, safety, and environmental protection, and certified with CE marking
Safety /EMC /EMI	IEC	Compliant to IEC 61010-1 for safety requirements for electrical equipment
	EN	Compliant to EN 61010-1 for safety requirements for electrical equipment
	IEC	Compliant to IEC 61326-1 for EMC requirements for electrical equipment
	EN	Compliant to EN 61326-1 for EMC requirements for electrical equipment
	EN	Compliant to EN 55011 for EMC requirements for industrial, scientific and medical equipment
RoHS	EU	Compliant to EU regulations Directive 2011/65/EU (RoHS 2) and Directive 2015/863 (RoHS 3)

Contact [Sales@AFLglobal.com](mailto:Sales@AFLglobal.com) to schedule a demonstration or learn how to buy.

Visit [www.AFLglobal.com/Test](http://www.AFLglobal.com/Test) to learn more about Optical Fiber Identifiers.

International Sales and Service Contact Information available at [www.AFLglobal.com/Test/Contacts](http://www.AFLglobal.com/Test/Contacts)