ROTRON / AMETEK®

ROTRON ½ AXIMAX® 2
Small Vaneaxial Fans


NORTH AMERICA
T: +1 845-679-1361
F: +1 845-679-1870

UNITED KINGDOM
T: +44 (0) 1932 765822
F: +44 (0) 1932 761098

EUROPE
T: +49 8145 951767
F: +49 8145 951768

ASIA PACIFIC
T: +65 6484 2388
F: +65 6481 6588

www.rotron.com




General Small Vaneaxial Information

Small Vaneaxial Fans are compact, high-speed fans whose airflow is parallel to the motor shaft. The impeller and guide vanes are of airfoil construction for maximum aerodynamic efficiency and minimum acoustical noise.

These fans are designed for use in tightly packaged airborne "black boxes" where sizes and weight must be held to an absolute minimum, where reliability is critical, and where high heat loads must be dissipated with cooling air.

Small Vaneaxial Fans come in a variety of voltages and frequencies and are available with lead wires, terminal blocks and MS connectors. Most units are available with an optional internal Fan Performance Sensor (FPS) or an external Low Speed Warning Device (LSWD).

Rotron ½ AXIMAX® 2



*Individual Performance Curve Characteristics Available Upon Request



General

- Physical envelope: 2.176" Dia. x 1.16"L1
- Weight: approximately 4.25 oz.
- Specially designed for electronics box cooling, such as avionics, radar, electronic counter-measures, displays, and communications equipment in aircraft, ground and shipboard applications
- Custom mounting configurations, such as flanges or servo rings and synclamps, are available[2]

[1] See specific part-number drawing for complete product dimensions
[2] Please contact the Application Engineering Department for further information

Materials and Finishes

- All aluminum components finished with a chemical conversion coating per MIL-C-5541, top coat of lusterless black enamel, color #37038, per Federal Standard 595 conforming to TT-E-489 Type B
- Corrosion-resistant stainless steel shaft and hardware
- Impeller runs on two high-precision, double-shielded, stainless steel ball bearings (ABEC Class 5) with an integral lubricant reservoir for a long, maintenance-free life
- Motors have stator winding insulation which is rated for continuous duty for Class H

Options/Accessories

- Finger Guard
- Synclamp
- LSWD (Low Speed Warning Device)
- FPS (Fan Performance Sensor)

AC Line Powered Units [1]

- 3-phase and 1-phase permanent-split capacitor motor designs
- Fixed speeds (performance) based on input frequency
- Meets or exceeds the requirements of MIL-B-23071 and other applicable U.S. military and commercial aerospace specifications[2]
- Max free delivery airflow of 32 CFM at 400 Hz
- Ambient temperature range: -54°C to 125°C
- Acoustic levels as low as 55 dBA

DC Line Powered Units – E.C.D.C® [1]

- Brushless permanent magnet design (Electronically Commutated DC)
- Speed (performance) fixed by input voltage
- Meets or exceeds the requirements of MIL-B-28873 and other applicable U.S. military and commercial aerospace specifications[2]
- Max free delivery airflow of 41.7 CFM
- Ambient temperature range: -54°C to 100°C
- Acoustic levels as low as 49.7 dBA

[1] Airflow, maximum ambient and acoustic levels will vary depending on design parameters
[2] Please call for further information concerning applicable U.S. military and commercial aerospace specifications

Optional DC-AC Inverters and AC-AC Converters for AC Powered Models[1]

BATAC® Inverter Driven Units

- AC square wave fans driven from a DC power source through a BATAC® Inverter
- Low cost alternative when multiple fans are used in a single application or area
- Allows for greater than 100 VDC input voltage


[1] See Accessories: Power Conversion

DELTAC® Converter Driven Units

- DELTAC® converters allow high frequency (typically 400 Hz) fans to be driven by variable frequency (typically 360-800 Hz) power or low frequency 50/60 Hz power to obtain the higher frequency performance

Unit Description Key

The unit description key is for reference only and should not be confused with a part number. While most units are custom configurations,not all variations of the key shown below are possible. Please contact the Application Engineering department for more information regarding possible custom configurations.



STD	CASE	BLADES
2	Std. Servo Rings	High Pitch, 4 Blades
2E	Std. Servo Rings	Low Pitch, 4 Blades
2A	Std. 3PT MTG	High Pitch, 4 Blades
2B	Std. 3PT MTG	Low Pitch, 4 Blades

EXAMPLE: AX1L, 115 AC, N, 415YH

* "X" IN ANY POSITION DENOTES SPECIAL FOR THAT FEATURE

Ordering Information

When ordering, please specify the specific Rotron part number listed on the model table below. Further ordering information, based on the configuration and motor series, may be obtained by contacting customer service. Please refer to the Unit Description Key explanation above.

Standard Product Offering of AC Line Powered Models


Part #	Prod. Desc.	Flow (CFM)	Max Pressure (IWG)	Nom. RPM	Nom. Watts	Line Amps (A)	Max Amb (°C)	Weight (lbs)	Volts	Phase	Hz	Capacitor	Airflow Source Data	Features
022035000	1/2 Aximax 2EL 729YH	32	2.5	21835	12	0.1	100	0.3	115	1	400	0.10/220	A411-15	LEADS
035373000	1/2 Aximax 2E 820JH	31	3.1	21500	20	0.1	100	0.3	200	3	400	N/A	A154-5	LEADS
034085000	1/2 Aximax 2L 795YH	25	0.6	10075	10	0.1	125	0.3	115	1	400	0.18/220	A225-11	LEADS

Standard Product Offering of DC Line Powered Models

Part #	Prod. Desc.	Fbw (CFM)	Max Pressure (IWG)	Nom. RPM	Nom. Watts	Line Amps (A)	Max Amb (°C)	Weight (lbs)	Volts (DC)	Airflow Source Data	Features
011611000	1/2 Aximax 2EL 2951SF	37	2.9	24000	17	0.65	85	0.4	28	A776-6A	Leads, FPS
011572000	1/2 Aximax 2L 3162SF	26	0.7	10000	7	0.25	85	0.4	28	A779-16C	Leads, FPS
011726000	1/2 Aximax 2 3052SF	21	1.2	15000	7	0.25	100	0.4	28	A778-20A	Leads, FPS


½ AXIMAX 2 – AC*

½AX2L



½ AXIMAX 2 – DC*

½AX2L



*Part Number Specific Drawings Available Upon Request

www.rotron.com

NORTH AMERICA
T: +1 845-679-1361
F: +1 845-679-1870

UNITED KINGDOM
T: +44 (0) 1932 765822
F: +44 (0) 1932 761098

EUROPE
T: +49 8145 951767
F: +49 8145 951768

ASIA PACIFIC
T: +65 6484 2388
F: +65 6481 6588

Specifications subject to change without notice