

100 SERIES GLIDING WINDOWS



Table of Gliding Window Sizes – Active-Stationary or Stationary-Active (X0/OX) Sash

Scale 1/8" (3) = 1'-0" (305) – 1:96


Window Dimension	1'-11 1/2"	2'-5 1/2"	2'-11 1/2"	3'-5 1/2"	3'-11 1/2"	4'-5 1/2"	4'-11 1/2"	5'-5 1/2"	5'-11 1/2"
	(597)	(749)	(902)	(1054)	(1207)	(1359)	(1511)	(1664)	(1816)
Minimum Rough Opening	2'-0"	2'-6"	3'-0"	3'-6"	4'-0"	4'-6"	5'-0"	5'-6"	6'-0"
	(610)	(762)	(914)	(1067)	(1219)	(1372)	(1524)	(1676)	(1829)
Unobstructed Glass (width of single sash)	7 9/16"	10 9/16"	13 9/16"	16 9/16"	19 9/16"	22 9/16"	25 9/16"	28 9/16"	31 9/16"
	(192)	(268)	(344)	(420)	(496)	(573)	(649)	(725)	(801)

CUSTOM WIDTHS – 23 1/2" to 71 1/2"


CUSTOM HEIGHTS – 11 1/2" to 71 1/2"	CUSTOM WIDTHS – 23 1/2" to 71 1/2"								
	2010	2610	3010	3610	4010	4610	5010	5610	6010
11 1/2" (292)									
1'-0" (305)									
1'-5 1/2" (445)									
1'-6" (457)									
1'-11 1/2" (597)									
2'-0" (610)									
2'-5 1/2" (749)									
2'-6" (762)									
2'-11 1/2" (902)									
3'-0" (914)									
3'-5 1/2" (1054)									
3'-6" (1067)									
3'-11 1/2" (1207)									
4'-0" (1219)									
4'-5 1/2" (1359)									
4'-6" (1372)									
4'-11 1/2" (1511)									
5'-0" (1524)									
5'-5 1/2" (1664)									
5'-6" (1676)									
5'-11 1/2" (1816)									
6'-0" (1829)									
6'-5 1/2" (1922)									



Custom-size windows are available in 1/8" (3) increments.



Active-Stationary



Stationary-Active

Choose active-stationary (X0) or stationary-active (OX) as viewed from the exterior. Two locks are standard on all heights greater than 4'-2" (1270).


*"Window Dimension" always refers to outside frame-to-frame dimension.
 **"Minimum Rough Opening" dimensions may need to be increased to allow for use of building wraps, flashing, sill panning, brackets, fasteners or other items.
 •Dimensions in parentheses are in millimeters.
 ◊Meets or exceeds clear opening area of 5.7 sq.ft. or 0.53 m²; clear opening width of 20" (508) and clear opening height of 24" (610).

Custom Sizes and Specification Formulas



100 Series custom-size windows are available in 1/8" (3) increments between minimum and maximum widths and heights shown. Some restrictions apply.

Gliding Windows



Active-Stationary or Stationary-Active (X0/OX)

Clear Opening 	Width = (window width + 2) - 3.711" (94) Height = window height - 3.500" (89)	Minimum R.O. 	Width = window width + 1/2" (13) Height = window height + 1/2" (13)
Vent Opening 	Width = (window width + 2) - 3.711" (94) Height = window height - 3.500" (89)	Unobst. Glass 	Fixed Sash Width = (window width + 2) - 4.184" (106) Venting Sash Width = (window width + 2) - 4.226" (107) Total Sash Width = window width - 8.410" (214) Height = window height - 6.250" (159)

• **Clear Opening** formulas provide dimensions for determining area available for egress. **Vent Opening** formulas provide dimensions for determining area available for passage of air. **Minimum R.O.** (minimum rough opening) formulas provide minimum rough opening width and height dimensions. **Unobst. Glass** (unobstructed glass) formulas provide dimensions for determining area available for passage of light.
 • Dimensions in parentheses are in millimeters.