

EU type examination certificate
EU-Baumusterprüfbescheinigung

CE-0085CL0072

Product Identification No.
 Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Distributor <i>Vertreiber</i>	BAXI S.p.A. Via Trozzetti, 20, I-36061 Bassano del Grappa (VI)
Product Category <i>Produktart</i>	Boilers with flue systems: Condensing water heater (3202)
Product Description <i>Produktbezeichnung</i>	Condensing boiler with fan-assisted burner and flue system
Model <i>Modell</i>	Power HT...
Countries of Destination <i>Bestimmungsländer</i>	AT, BA, BE, BG, BY, CH, CN, CY, CZ, DK, EE, ES, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, RS, RU, SE, SI, SK, TR, UA
Test Reports <i>Prüfberichte</i>	supplement test: K 864 2018 E12 from 06.07.2018 (TRG) supplement test: K 864 2018 B13 from 06.07.2018 (TRG)
Test Basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 15502-1 (01.10.2015) DIN EN 15502-2-1 (01.09.2017)

Date of Expiry / File No. 02.02.2028 / 18-0543-GEA
Ablaufdatum / AZ

70028-04-A-DE

17.08.2018 Rie D-1/2

Date, Issued by, Sheet, Head of Certification Body
 Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EU Regulation



DVGW CERT GmbH
 Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
 53123 Bonn

Tel. +49 228 91 88 - 888
 Fax +49 228 91 88 - 993

www.dvgw-cert.com
 info@dvgw-cert.com

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EU-Verordnung EU/2016/426.

Elektrical Data 230 V AC, 50 Hz, IP22
Elektrische Daten

Appliance Categories <i>Gerätekatégorien</i>	Supply Pressures <i>Versorgungsdrücke</i>	Countries of Destination <i>Bestimmungsländer</i>	Remarks <i>Bemerkungen</i>
I2E	20 mbar	PL	
I2E(R)	20/25 mbar	BE	
I2E(S)	20/25 mbar	BE	only types ...1.115 up to 1.320
I2ELw	20 mbar	PL	only types ...1.115 up to 1.320
I2Esi	20/25 mbar	FR	
I2H	20 mbar	AT, BG, CH, CZ, DK, EE, ES, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, NO, PT, RO, SE, SI, SK, TR	
I2HS	25 mbar	HU	
I2L	25 mbar	NL	
I3P	30 mbar	BE	only types ...1.115 up to 1.320
I3P	37 mbar	BE	only types ...1.115 up to 1.320
II2E3B/P	20, 50 mbar	LU	only types ...1.115 up to 1.320
II2ELwLs3B/P	20,20,13, 30 mbar	PL	only types ...1.115 up to 1.320
II2ELwLs3B/P	20,20,13, 37 mbar	PL	only types ...1.115 up to 1.320
II2Esi3P	20/25, 30 mbar	FR	only types ...1.115 up to 1.320
II2Esi3P	20/25, 37 mbar	FR	only types ...1.115 up to 1.320
II2H3+	20, 28-30/37 mbar	ES, IT	only types ...1.115 up to 1.320
II2H3B/P	20, 30 mbar	CH, CY, CZ, DK, EE, GB, GR, IE, IS, RO, SE, SI, SK, TR	only types ...1.115 up to 1.320
II2H3B/P	20, 37 mbar	CH, CY, CZ, GB, GR, IE, IS, LT, NO, SI, SK, TR	only types ...1.115 up to 1.320
II2H3B/P	20, 50 mbar	AT, CH, CZ, GB	only types ...1.115 up to 1.320
II2HS3B/P	25, 30 mbar	HU	only types ...1.115 up to 1.320
II2HS3B/P	25, 50 mbar	HU	only types ...1.115 up to 1.320
II2L3P	25, 30 mbar	NL	only types ...1.115 up to 1.320
II2L3P	25, 50 mbar	NL	only types ...1.115 up to 1.320

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
HT-A 1.115	nominal heat output: 19,2...110,9 kW heat input (Hi): 20,0...114,0 kW	
HT-A 1.135	nominal heat output: 19,2...121,6 kW heat input (Hi): 20,0...125,0 kW	
HT-A 1.180	nominal heat output: 26,8...165,8 kW heat input (Hi): 28,0...170,0 kW	
HT-A 1.230	nominal heat output: 33,5...210,1 kW heat input (Hi): 35,0...215,0 kW	
HT-A 1.280	nominal heat output: 40,2...254,5 kW heat input (Hi): 42,0...260,0 kW	
HT-A 1.320	nominal heat output: 47,1...294,3 kW heat input (Hi): 48,0...300,0 kW	
HT-A 1.430	nominal heat output: 80,4...393,8 kW heat input (Hi): 82,0...402,0 kW	
HT-A 1.500	nominal heat output: 93,0...459,0 kW heat input (Hi): 95,0...469,0 kW	
HT-A 1.570	nominal heat output: 106,6...526,9 kW heat input (Hi): 109,0...539,0 kW	
HT-A 1.650	nominal heat output: 119,2...595,7 kW heat input (Hi): 122,0...610,0 kW	

Hints of Utilization /Remarks

Verwendungshinweise / Bemerkungen

Additionally tested appliance categories, supply pressures and countries of destination:

BA, BY, CN, MT, RS, RU, UA: I2H (20 mbar)

BG (only types ...1.115 up to 1.320): II2H3B/P (20, 30 mbar)

PT (only types ...1.115 up to 1.320): II2H3B/P (20, 37 mbar)

In Bosnia and Herzegovina, China, Serbia, in the Russian Federation, in the Ukraine and in Belarus the CE-marking will be accepted as conformaty approval if the Gas Appliance Regulation EU/2016/426 is transferred into national law by Bosnia and Herzegovina, China, Serbia, the Russian Federation, Ukraine respectively Belarus

flue types B23, B23P, C13, C33, C43, C53, C63, C83, C93: according to installation manual "Power HT" with flue system SAS