

Quinta Ace 115

Technical data sheet



This is a quick reference technical data sheet, full details can be found within the Quinta ACE installation and user manual via www.baxi.co.uk

Date: January 2025

Overview		ErP Data: ^Energy Label / ^^Eco Design	
Model: Quinta Ace 115	PIN ID No: 0063DP3280	Seasonal Space Efficiency % ⁽²⁾	N/A
Rated Output (80/60°C)	103.9 kW	Energy Efficiency Class ⁽²⁾	N/A
Rated Output (50/30°C)	109.7 kW	Sound Power Levels Lwa	59 dB [^] (indoors)
Weight (dry) without packaging	68 kgs (without front casing)	Annual Energy Consumption	N/A
Overall Dim WxHxD	500x750x476 mm	Useful Efficiency - Full Load (GCV) ⁽³⁾	87.5 [^]
No of sections	One piece casting	Useful Efficiency - Part Load (GCV) ⁽³⁾	97.3 [^]
SBEM Seasonal Efficiency %: GCV ⁽¹⁾	95.4	Hydraulics	
Efficiency - Full Load 100%: NCV ⁽⁴⁾	97.1	Water contents	9.4 ltrs
Efficiency - Part Load 30%: NCV ⁽⁵⁾	108.0	Resistance @ 15°C	444 mbar
Stand-by Heat Loss	0.123 kW	Resistance @ 20°C	250 mbar
Burner type pre-mix		Nominal Flow Rate @ 15°C	1.66 l/s
Standard Fuel Available	Natural Gas	Nominal Flow Rate @ 20°C	1.24 l/s
Fuel Consumption (max) NG	11.1 m3/h	Condensate Connection	22.5mm OD
Fuel Consumption (max) LPG	4.2 m3/h	Flow Connection Size BSP	1 1/4"(M)
Flame Protection	Ionisation	Return Connection Size BSP	1 1/4"(M)
Ignition	Electronic	Standard Operating Temp.	20-90oC (**)
Acoustic level at 1 metre	51.1 dB(A)	Maximum Operating Temp.	90oC (**)
Optional Fuel (*)	Propane	High Limit Set Point	110oC (**)
Gas Connection size BSP	3/4" (M)	Maximum operating pressure	4 bar
Min/Max Gas pressure - NG	17-25 mbar	Minimum operating pressure	0.8 bar
Min/Max Gas pressure - LPG	37-50 mbar	Minimum operating pressure	0.3 bar (Open Vent)
NOx Annual Emissions - NG BREEAM (EN15502)	23 mg/kWh (dry, 0% O ₂) - Class 6	Electrical	
Concentric flue/air inlet		Electrical	230v - 1ph - 50hz
Flue diameter I/D (***)	100 mm	Full Load Current	0.70 amps
Air inlet diameter I/D (#)	150 mm	Power Consumption	19 - 169 W
Mass flue gas flow rate	36-178 kg/hr	Modulating input	0-10 v dc
Flue gas temperature	30-72°C	Controls Voltage (Potential free Contact)	0 v
Maximum counter pressure	220 Pa	Insulation Class IP	X4D

Standard
 - On/Off, 0-10v dc, Open Therm, R-Bus
 - High limit protection and low water protection
 - Volt free common alarm and boiler run indication
 - Manual Override
 - Hot water priority facility (3 way valve or pump)
 - Two Safety Interlocks
 - Hours run indication
 - Flue - concentric connection (**) (#)
 - LIN-Bus (Pump protocols)
 - Quick connect external sockets

Optional
 - Optimising compensator for single and multiple boilers
 - Cascade kits - multiple boiler pipework kits
 - Low loss headers
 - Plate heat exchangers
 - Air dirt separators
 - ModBus & BACNet communications gateway
 - Outside sensor for simple weather compensation
 - Hot water priority kits (QA 30 - 115 only)
 - Pump and valve kits
 - Relay kits for single and multiple controls where a 230v switching relay is required

1) In accordance with the Approved Document Part L2 Building Regulations 2021 Edition - For use in England
 (2) In accordance with EU 811 & 812 / 2013 Energy Labeling Regulations
 (3) In accordance with EU 813 & 814 / 2013 Eco Design Regulations
 (4) @ 80/60°C Nett (EN 15502-1 & -2)
 (5) @ 50/30°C Nett (EN 15502-1 & -2)

(*) See installation and service manual
 (**) Open vented option maximum operating temperature 75°C high limit 95°C
 (***) For conventional or room sealed operation
 (#) Flue adaptor available for CLV systems
 GAR (EU) 2016/426
 BED 92/42/EEC
 EMC 2014/30/EU
 LVD 2014/35/EU
 ErP 2009/125/EC