

Product fiche for boiler space heaters

Baxi 800 Heat		816	825	830
Seasonal space heating energy efficiency class		A	A	A
Rated heat output (<i>Prated or Psup</i>)	kW	16	25	30
Seasonal space heating energy efficiency	%	93	93	93
Annual energy consumption	kWh	13764	21506	25807
	GJ	50	77	93
Sound power level L_{WA} indoors	dB	39	45	49

Package fiche for boilers indicating the space heating energy efficiency of the package

Seasonal space heating energy efficiency of boiler

$$\text{I} \quad \boxed{} \%$$

Temperature control

from fiche of temperature control

Class I = 1%, Class II = 2%, Class III = 1.5%,
Class IV = 2%, Class V = 3%, Class VI = 4%,
Class VII = 3.5%, Class VIII = 5%

$$+ \text{II} \quad \boxed{} \%$$

Supplementary boiler

from fiche of boiler

Seasonal space heating energy efficiency (in %)

$$\left(\boxed{} - \text{I} \right) \times 0.1 = \pm \text{III} \quad \boxed{} \%$$

Solar contribution

from fiche of solar device

Collector size (in m²)

Tank volume (in m³)

Collector efficiency (in %)

Tank rating ⁽¹⁾
A* = 0.95, A = 0.91,
B = 0.86, C = 0.83,
D - G = 0.81

$$\left(\text{III} \times \boxed{} + \text{IV} \times \boxed{} \right) \times 0.9 \times \left(\boxed{} / 100 \right) \times \boxed{} = + \text{IV} \quad \boxed{} \%$$

(1) If tank rating is above A, use 0.95

Supplementary heat pump

from fiche of heat pump

Seasonal space heating energy efficiency (in %)

$$\left(\boxed{} - \text{I} \right) \times \text{II} = + \text{V} \quad \boxed{} \%$$

Solar contribution AND Supplementary heat pump


select smaller value

$$0.5 \times \text{IV} \quad \boxed{} \quad \text{OR} \quad 0.5 \times \text{V} \quad \boxed{} = - \text{VI} \quad \boxed{} \%$$

Seasonal space heating energy efficiency of package

$$\text{VII} \quad \boxed{} \%$$

Seasonal space heating energy efficiency class of package



Boiler and supplementary heat pump installed with low temperature heat emitters at 35°C ?

from fiche of heat pump

$$\text{VII} \quad \boxed{} + (50 \times \text{II}) = \boxed{} \%$$

The energy efficiency of the package of products provided for in this fiche may not correspond to its actual energy efficiency once installed in a building, as this efficiency is influenced by further factors such as heat loss in the distribution system and the dimensioning of the products in relation to building size and characteristics.

- I The value of the seasonal space heating energy efficiency of the preferential space heater, expressed in %.
- II The factor for weighting the heat output of preferential and supplementary heaters of a package as set out in the following table.

- III The value of the mathematical expression: $294/(11 \cdot \text{Prated})$, whereby 'Prated' is related to the preferential space heater.
- IV The value of the mathematical expression $115/(11 \cdot \text{Prated})$, whereby 'Prated' is related to the preferential space heater.

Weighting of boilers

$P_{sup} / (Prated + P_{sup})^{(1)(2)}$	II, package without hot water storage tank	II, package with hot water storage tank
0	0	0
0.1	0.3	0.37
0.2	0.55	0.70
0.3	0.75	0.85
0.4	0.85	0.94
0.5	0.95	0.98
0.6	0.98	1.00
≥ 0.7	1.00	1.00

(1) The intermediate values are calculated by linear interpolation between the two adjacent values.
(2) Prated is related to the preferential space heater or combination heater.

Package efficiency

Baxi 800 Heat		816	825	830
Temperature control X	%			
Temperature control Y	%			