

# Baxi Auriga HP 26T

## 7832029

# BAXI

Further information can be found at [baxi.co.uk/auriga](http://baxi.co.uk/auriga)

Date: Feb 24

Performance	26kW
Heating capacity at A7/W35	27.2 kW
Power input at A7/W35**	6.33
COP at A7/W35	4.3
Heating capacity at A-10/W35	17.54kW
Power input at A-10/W35**	6.42
COP at A-10/W35	2.73
SCOP at Water 35	4.31
SCOP at Water 55	3.47
Seasonal efficiency at Water 35	170%
Seasonal efficiency at Water 55	136%

ERP Data	
Energy label rating at Water 55	A++
Sound power rating at A7/W55	65 dB(A)

Refrigerant	
Refrigerant type	R32
Refrigerant weight	4.8 kg
Refrigerant GWP	675
Equivalent CO <sub>2</sub>	3.24 Tn

Hydraulics	
Nominal volume flow rate	1.31 l/s
Minimum volume flow rate	0.83 l/s
Water Temperature min/max	+25/+58° C
Available Water Pressure	3.2 mca
Max operating pressure	6 bar
Min operating pressure	0.5 bar
Max supply temperature	60° C
Flow connection size	1 1/4 Inch
Return connection size	1 1/4 Inch
Circulation pump integrated	Yes
Pressure relief valve integrated	Yes
Expansion vessel integrated	No

Source Data	26kW
Operating limits, source [air]	-20 to +40° C
Nominal volume flow rate, source	8500 m <sup>3</sup> /h

Electrical	
Protection class	IP 24

Power Source	
Power supply compressor	3 Phase + Neutral 50 Hz
Nominal voltage compressor	400 V
Nominal voltage fans	400 V
Number of compressors	1 x Scroll Inverter
Number of fans	2 x DC Inverter
Starting current	7.0 A
Minimum Cable Size****	6mm <sup>2</sup>
Max operating current FLC	30 A
Circuit Protection Type	32 A Type C

General	
Nominal Sound power level LwA*	69 dB(A)
Nominal Sound pressure LpA @5m	43 dB(A)
Unit dimensions (mm)	1276 Height 1612 Width 707 Depth
Unit weight dry	271 kg
Service clearances (mm)	1500 Front 600 Rear 800 Left Side 800 Right Side

\* In accordance with EN 9614-2 under condition A7/W55. \*\* Calculated from Line to Line voltage of 400v and a Power Factor of 0.85. \*\*\* Ensure a flexible pipe is utilized for the flow and return connections to prevent vibration transmission. A water filter must be installed on the return line to the appliance. \*\*\*\* The wiring installation must comply with BS 7671, cable size may need to be increased depending on length of cable, cable type and any other installation factors that need to be taken into account. © Ours is a policy of continuous development, we therefore reserve the right to alter specification without prior notification. Baxi accept no liability for any loss or damage arising from any errors or omissions that may be inadvertently contained in this specification sheet.