

# E-HP AW 88 Ace B specification.

Further information can be found at [remeha.co.uk/documents](http://remeha.co.uk/documents)

Date: **March 2022**

Performance	88 ACE B
Heating capacity at A7/W35	68.64 kW
Power input at A7/W35	15.24 kW
COP at A7/W35	4.5
Heating capacity at A-7/W35	47.03 kW
Power input at A-7/W35	14.6 kW
COP at A-7/W35	3.22
SCOP average climate low temperature	4.26
SCOP average climate high temperature	3.22
Seasonal efficiency low temperature	168%
Seasonal efficiency high temperature	126%

ERP Data	
Energy label rating average climate	A++
Sound power rating indoors/outdoors LAW	0/67 dB

Refrigerant	
Refrigerant type	R407c
Refrigerant weight	17 kg
Refrigerant GWP	1774
Equivalent CO <sub>2</sub>	30.2 T

Hydraulics	
Nominal volume flow rate, sink***	3.3 l/s
Minimum volume flow rate, sink***	1.64 l/s
Flow and return ΔT	5-10°C
Pressure drop @ nominal flow rate	25 kPa
Max operating pressure	10 bar
Min operating pressure	2 bar
Max supply temperature	65°C
Flow connection size	2 Inch
Return connection size	2 Inch
Circulation pump integrated	No
Pressure relief valve integrated	No
Expansion vessel integrated	No

Source Data	44 ACE B
Operating limits, source [air]	-20 to +35°C
Nominal volume flow rate, source	17100 m <sup>3</sup> /h

Electrical	
Protection class	IP42
	3 + Neutral Phases
Power supply compressor	50 Hz
	400 V
Nominal voltage compressor	400 V
Nominal voltage fans	230 V
Power supply controller 1 phase + neutral	230 V
Number of compressors	2
Number of fans	4
Starting current with soft starter 1st compressor	73.6 A
Starting current with soft starter 2nd compressor**	100 A
Power input controller	15 kW
Max operating current FLC	53.4 A
Nominal current (A7 & W55)*	38.2 A

General	
Sound power level LwA*	67 dB(A)
Sound pressure level LpA	81.5
	1550 Height
Unit dimensions (mm)	2310 Width
	1365 Depth
Unit weight dry	790 kg
	2000 Front
Service clearances (mm)	2000 Rear
	1500 Left Side
	1500 Right Side

\* In accordance with EN 9614-2 under condition A7/W55.

\*\* The accumulated starting current is calculated with the starting current of the second compressor and the maximum operating current (MCC) of the first compressor, seen as the worst case scenario.

\*\*\* The circulating pump for the ASHP must be capable of accepting a 0-10v speed control signal from the appliance, the pump must have sufficient modulation to meet both the nominal and minimum flow rates.

© Ours is a policy of continuous development, we therefore reserve the right to alter specification without prior notification. Remeha accept no liability for any loss or damage rising from any errors or omissions that may be inadvertently contained in this specification sheet.