

# P520/17 specification.

Further information can be found at [remeha.co.uk/documents](http://remeha.co.uk/documents)

Date: June 2022

Overview	P520
Rated output kW	928-986
Weight (dry) kg	3756
Overall dim WxHxD mm	1172 x 1760 x 2445
Radiated losses %*	0.07
Efficiency % : NCV full load <sup>(3)</sup>	90
Seasonal efficiency : % GCV	84.3

Burner type – pressure jet	
Fuel available	Nat gas
Fuel consumption : max	Check burner details
Noise levels dB(A)	Check burner details
Min op gas press mbar	Check burner details

Flue/Air inlet	
Diameter mm	400
Flue type	Conventional
Chamber resist mbar	+2.6
Flue gas flow kg/hr gas : <sup>(1)</sup>	1440
Flue gas flow kg/hr oil : <sup>(1)</sup>	1370
Flue gas temperature °C: <sup>(2)</sup>	< 190

Control/options	
Standard	Optional
On/off thermostat High limit thermostat High/low indication Temperature indication Volt-free run/lock indication Three-position switch auto/man/test L/O lamp On/off switch 10 amp CB	Hours run meters Modulating (via burner)

Hydraulics	
Water content ltrs	769
Resistance @11°C mbar	25.10
Resistance @20°C mbar	7.6
Nom flow rate @11°C l/s	21.41
Nom flow rate @20°C l/s	11.78
Min flow rate l/s : #	5.21
Max op press bar	As per technical manual
Test press bar	As per assembly manual
Min return temp °C	50
Connection size (weld) mm	140
Std operating temp °C	80
Max operating temp °C	90
High limit set point °C	110

Electrical	
Voltage	230.1.50
Fuse rating	10 Amp circuit breaker

Note: 1ph burners obtain their power supply via the boiler. 3ph burners require a 3ph supply + a 1ph to the boiler

Quick reference specification sheet, full details can be found in the P520 series installation/service guide. General details: Corrosion resistant cast iron sectional boiler, jointed by conical nipples and ceramic rope, designed with three passes for high efficiency and low NO<sup>x</sup> emission. Large insulated door (hinged left or right) allowing easy access for cleaning. Powder coated enamel steel casing c/w fibreglass insulation. All of the P520 boiler range are supplied unassembled for delivery to site. CE approved. Boiler efficiency data to 92/42-EEC.

(1) Boiler at full output average temperature 80/30°C (70°C mean)

(2) With boiler temperature: 80°C and ambient temperature: 20°C

(3) 70°C mean temperature

\*Maintenance consumption refer to boiler installation/service manual

# Based delta tof 45°C between the boiler and the room temperature

## @12 bar pump pressure

© Ours is a policy of continuous development, we therefore reserve the right to alter specification without prior notification. Remeha accept no liability for any loss or damage rising from any errors or omissions that may be inadvertently contained in this specification sheet.