

COLLECTION: KIDGLOVE

DESIGN: KIDGLOVE

## BASIC INFORMATION

|                              |            |                                     |                 |
|------------------------------|------------|-------------------------------------|-----------------|
| Brand                        | FibreGuard | Number of colour ways               | 38              |
| Tariff item number           | 5407520000 | MID                                 | CNTONFOR1202TON |
| Country of origin            | China      | Characteristics                     | Flat Weave      |
| Vertical repeat cm           | Plain      | Vertical repeat inch                | Plain           |
| Horizontal repeat cm         | Plain      | Horizontal repeat inch              | Plain           |
| Face in                      | Yes        | Full roll diameter cm               | 21              |
| Full roll diameter inch      | 8.27       | Average piece length m              | 50              |
| Minimum for special colour m | 1000       | Delivery time weeks special lab dip | 2               |

## CARE CODES



## CARE AND USAGE

### Use codes

|             |     |                        |     |
|-------------|-----|------------------------|-----|
| Curtains    | Yes | Curtains and draperies | Yes |
| Upholstery  | Yes | Bed covering           | Yes |
| Accessories | Yes |                        |     |

## ENVIRONMENTAL STANDARDS



STANDARD  
100  
2111231  
Centexbel



### Labels

|                   |     |         |     |
|-------------------|-----|---------|-----|
| GRS post-consumer | Yes | Prop 65 | Yes |
|-------------------|-----|---------|-----|

COLLECTION: KIDGLOVE

DESIGN: KIDGLOVE

## FR STANDARDS

|                  |     |          |     |
|------------------|-----|----------|-----|
| BS 5852 Source 0 | Yes | CAL 117  | Yes |
| FMVSS 302        | Yes | NFPA 260 | Yes |

## FABRIC SPECIFICATIONS

|                          |                                       |                     |               |
|--------------------------|---------------------------------------|---------------------|---------------|
| Composition              | 60% Recycled Polyester, 40% Polyester | Average yarn number | 10.19         |
| Construction             | 14x13                                 | Woven               | Yes           |
| Useable width cm         | 142                                   | Useable width inch  | 55.91         |
| Full width cm            | 144                                   | Full width inch     | 56.69         |
| Weight g/m <sup>2</sup>  | 265                                   | Thickness mm        | 0.720         |
| Colouring type           | Piece dyed                            | Filament or staple  | 100% filament |
| Textured or non textured | 100% textured                         |                     |               |

### Treatment

|                       |     |         |     |
|-----------------------|-----|---------|-----|
| Brushed/emersed       | Yes | Backing | Yes |
| Stain free technology | Yes |         |     |

### Type of finish

There are no technical details for this section.

### Type of print or dye

|     |     |
|-----|-----|
| Vat | Yes |
|-----|-----|

### Weaving type

|       |     |
|-------|-----|
| Dobby | Yes |
|-------|-----|

COLLECTION: KIDGLOVE

DESIGN: KIDGLOVE

## MECHANICAL PERFORMANCE

|                                   |         |                                             |        |
|-----------------------------------|---------|---------------------------------------------|--------|
| Martindale rubs                   | 50,000  | Colour fastness to light                    | 4      |
| Wyzenbeek double rubs             | 100,000 | Pilling                                     | 3-4    |
| Brush pilling                     | 4       | Wyzenbeek wire screen double rubs           | 15,000 |
| Wyzenbeek cotton duck double rubs | 100,000 | Wyzenbeek cotton duck type heavy upholstery | Yes    |
| Wyzenbeek wire screen heavy duty  | Yes     |                                             |        |

### Colour fastness to light – ISO 105-B02

|                          |   |
|--------------------------|---|
| Colour fastness to light | 4 |
|--------------------------|---|

### Colour fastness to weathering – ISO 105-B04:1994

There are no technical details for this section.

### Colour fastness to water – ISO 105-E01

|                          |   |
|--------------------------|---|
| Colour fastness to water | 5 |
|--------------------------|---|

### Colour fastness to dry rub – ISO 105-X12

|                         |     |
|-------------------------|-----|
| Colour fastness dry rub | 4-5 |
|-------------------------|-----|

### Colour fastness to wet rub – ISO 105-X12

|                         |     |
|-------------------------|-----|
| Colour fastness wet rub | 4-5 |
|-------------------------|-----|

### Tearing strength – ISO 13937-3

|                         |    |                         |    |
|-------------------------|----|-------------------------|----|
| Tearing strength warp N | 72 | Tearing strength weft N | 96 |
|-------------------------|----|-------------------------|----|

### Tensile strength – ISO 13934-1

|                             |      |                             |     |
|-----------------------------|------|-----------------------------|-----|
| Tensile strength warp N/5cm | 1200 | Tensile strength weft N/5cm | 680 |
|-----------------------------|------|-----------------------------|-----|

### Elongation – ISO 13934-1

|                   |      |                   |    |
|-------------------|------|-------------------|----|
| Elongation warp % | 35.5 | Elongation weft % | 33 |
|-------------------|------|-------------------|----|

### Seam slippage – ISO 13936-2

|                       |   |                       |   |
|-----------------------|---|-----------------------|---|
| Seam slippage warp mm | 2 | Seam slippage weft mm | 2 |
|-----------------------|---|-----------------------|---|

### Dimensional stability (indicated in %) – ISO 3759

|                                                     |       |                                                     |      |
|-----------------------------------------------------|-------|-----------------------------------------------------|------|
| Dimensional change warp                             | 0.00  | Dimensional change warp after ironing with steam    | 0.00 |
| Dimensional change warp after ironing without steam | 0.00  | Dimensional change weft                             | 0.07 |
| Dimensional change weft after ironing with steam    | -0.08 | Dimensional change weft after ironing without steam | 0.00 |

COLLECTION: KIDGLOVE

DESIGN: KIDGLOVE

## ACOUSTICS

### Sound absorption performance for drapery

There are no technical details for this section.

### Sound absorption performance for upholstery

There are no technical details for this section.

### Sound transmission

There are no technical details for this section.

## WASHABILITY

### Resistance to domestic washing 30° C, indicated in % - ISO 6330

|                             |       |                                       |      |
|-----------------------------|-------|---------------------------------------|------|
| Dimensional change warp     | -0.03 | Dimensional change warp after ironing | 0.00 |
| Dimensional change weft     | 0.20  | Dimensional change weft after ironing | 0.33 |
| Colour fastness ISO 105 C06 | 4-5   |                                       |      |

### Resistance to domestic washing 40° C, indicated in % - ISO 6330

|                         |      |                                       |      |
|-------------------------|------|---------------------------------------|------|
| Dimensional change warp | 0.00 | Dimensional change warp after ironing | 0.00 |
| Dimensional change weft | 0.00 | Dimensional change weft after ironing | 0.00 |

### Resistance to domestic washing 60°C, indicated in % - ISO 6330

|                             |       |                                       |       |
|-----------------------------|-------|---------------------------------------|-------|
| Dimensional change warp     | -1.33 | Dimensional change warp after ironing | -1.20 |
| Dimensional change weft     | -0.53 | Dimensional change weft after ironing | -0.53 |
| Colour fastness ISO 105 C06 | 4-5   |                                       |       |

### Resistance to domestic washing 74 C ISO 6330

|                             |       |                                       |      |
|-----------------------------|-------|---------------------------------------|------|
| Dimensional change warp     | -3.00 | Dimensional change warp after ironing | 0.00 |
| Dimensional change weft     | -1.60 | Dimensional change weft after ironing | 0.00 |
| Colour fastness ISO 105 C06 | 4-5   |                                       |      |

### Resistance to dry cleaning P, indicated in % - ISO 105 D01

|                             |       |                                       |       |
|-----------------------------|-------|---------------------------------------|-------|
| Dimensional change warp     | -1.46 | Dimensional change warp after ironing | -0.53 |
| Dimensional change weft     | -0.83 | Dimensional change weft after ironing | -0.53 |
| Colour fastness ISO 105 D01 | 4-5   |                                       |       |

COLLECTION: KIDGLOVE

DESIGN: KIDGLOVE

CONSTRUCTION

Yarn 1

|                           |                                       |                  |     |
|---------------------------|---------------------------------------|------------------|-----|
| Warp Composition          | 60% Recycled Polyester, 40% Polyester | Warp Is Filament | Yes |
| Warp Is Not High Tenacity | Yes                                   | Warp Is Staple   | No  |
| Warp Sizes                | 960D                                  | Warp Textured    | Yes |
| Warp Threads per cm       | 14                                    | Warp TPM         | 0   |

Yarn 2

|                           |                                       |                  |     |
|---------------------------|---------------------------------------|------------------|-----|
| Weft Composition          | 60% Recycled Polyester, 40% Polyester | Weft Is Filament | Yes |
| Weft Is Not High Tenacity | Yes                                   | Weft Is Staple   | No  |
| Weft Sizes                | 960D                                  | Weft Textured    | Yes |
| Weft Threads per cm       | 13                                    | Weft TPM         | 0   |

DOWNLOADS

-  [KIDGLOVE-Cal TB 117-2013-41827](#)
-  [KIDGLOVE-NFPA 260 UFAC-41827](#)
-  [Kidglove - FibreGuard report](#)
-  [KIDGLOVE-FMVSS302-41827](#)
-  [Kidglove 23073154A Bru Textiles BS 5852 Source 0](#)

