

COLLECTION: VELVELUX

DESIGN: VELVELUX

## BASIC INFORMATION

|                              |            |                                     |                |
|------------------------------|------------|-------------------------------------|----------------|
| Brand                        | FibreGuard | Number of colour ways               | 35             |
| Tariff item number           | 5801370000 | MID                                 | INDDEHOM167MUM |
| Country of origin            | India      | Characteristics                     | Velvet         |
| Vertical repeat cm           | Plain      | Vertical repeat inch                | Plain          |
| Horizontal repeat cm         | Plain      | Horizontal repeat inch              | Plain          |
| Face in                      | Yes        | Full roll diameter cm               | 27             |
| Full roll diameter inch      | 10.63      | Average piece length m              | 30             |
| Minimum for special colour m | 1000       | Delivery time weeks special lab dip | 2              |
| Suspended box                | Yes        |                                     |                |

## CARE CODES



## CARE AND USAGE

## Use codes

|             |     |                        |     |
|-------------|-----|------------------------|-----|
| Curtains    | Yes | Curtains and draperies | Yes |
| Upholstery  | Yes | Bed covering           | Yes |
| Accessories | Yes |                        |     |

## ENVIRONMENTAL STANDARDS



STANDARD  
100  
2111231  
Centexbel



ISO 14001  
Environmental  
Management

## Labels

|                   |     |
|-------------------|-----|
| GRS post-consumer | Yes |
|-------------------|-----|

COLLECTION: VELVELUX

DESIGN: VELVELUX

## FR STANDARDS

|                  |     |                                   |     |
|------------------|-----|-----------------------------------|-----|
| BS 5852 Source 0 | Yes | BS 5852 Source 1 (with treatment) | Yes |
| CAL 117          | Yes | EN 1021-2 (with treatment)        | Yes |
| FMVSS 302        | Yes | NFPA 260                          | Yes |

## FABRIC SPECIFICATIONS

|                          |                         |                     |               |
|--------------------------|-------------------------|---------------------|---------------|
| Composition              | 100% Recycled Polyester | Average yarn number | 13.39         |
| Construction             | 22.44x29.92             | Woven               | Yes           |
| Useable width cm         | 147                     | Useable width inch  | 57.87         |
| Full width cm            | 149                     | Full width inch     | 58.66         |
| Weight g/m <sup>2</sup>  | 391                     | Thickness mm        | 1.510         |
| Colouring type           | Piece dyed              | Filament or staple  | 100% filament |
| Textured or non textured | 100% textured           |                     |               |

### Treatment

|                       |     |
|-----------------------|-----|
| Stain free technology | Yes |
|-----------------------|-----|

### Type of finish

|         |     |
|---------|-----|
| Stenter | Yes |
|---------|-----|

### Type of print or dye

|          |     |
|----------|-----|
| Disperse | Yes |
|----------|-----|

### Weaving type

|       |     |
|-------|-----|
| Dobby | Yes |
|-------|-----|

COLLECTION: VELVELUX

DESIGN: VELVELUX

## MECHANICAL PERFORMANCE

|                                   |         |                                             |        |
|-----------------------------------|---------|---------------------------------------------|--------|
| Martindale rubs                   | 100,000 | Colour fastness to light                    | 6      |
| Wyzenbeek double rubs             | 100,000 | Pilling                                     | 5      |
| Brush pilling                     | 5       | Wyzenbeek wire screen double rubs           | 15,000 |
| Wyzenbeek cotton duck double rubs | 100,000 | Wyzenbeek cotton duck type heavy upholstery | Yes    |
| Wyzenbeek wire screen heavy duty  | Yes     |                                             |        |

### Colour fastness to light – ISO 105-B02

|                          |   |
|--------------------------|---|
| Colour fastness to light | 6 |
|--------------------------|---|

### Colour fastness to weathering – ISO 105-B04:1994

There are no technical details for this section.

### Colour fastness to water – ISO 105-E01

|                          |     |
|--------------------------|-----|
| Colour fastness to water | 4-5 |
|--------------------------|-----|

### Colour fastness to dry rub – ISO 105-X12

|                         |     |
|-------------------------|-----|
| Colour fastness dry rub | 4-5 |
|-------------------------|-----|

### Colour fastness to wet rub – ISO 105-X12

|                         |     |
|-------------------------|-----|
| Colour fastness wet rub | 4-5 |
|-------------------------|-----|

### Tearing strength – ISO 13937-3

|                         |    |                         |    |
|-------------------------|----|-------------------------|----|
| Tearing strength warp N | 46 | Tearing strength weft N | 72 |
|-------------------------|----|-------------------------|----|

### Tensile strength – ISO 13934-1

|                             |      |                             |     |
|-----------------------------|------|-----------------------------|-----|
| Tensile strength warp N/5cm | 1300 | Tensile strength weft N/5cm | 910 |
|-----------------------------|------|-----------------------------|-----|

### Elongation – ISO 13934-1

|                   |    |                   |    |
|-------------------|----|-------------------|----|
| Elongation warp % | 38 | Elongation weft % | 35 |
|-------------------|----|-------------------|----|

### Seam slippage – ISO 13936-2

|                       |   |                       |   |
|-----------------------|---|-----------------------|---|
| Seam slippage warp mm | 2 | Seam slippage weft mm | 2 |
|-----------------------|---|-----------------------|---|

### Dimensional stability (indicated in %) – ISO 3759

|                                                     |      |                                                     |      |
|-----------------------------------------------------|------|-----------------------------------------------------|------|
| Dimensional change warp                             | 0.02 | Dimensional change warp after ironing with steam    | 0.00 |
| Dimensional change warp after ironing without steam | 0.00 | Dimensional change weft                             | 0.15 |
| Dimensional change weft after ironing with steam    | 0.00 | Dimensional change weft after ironing without steam | 0.00 |

COLLECTION: VELVELUX

DESIGN: VELVELUX

## ACOUSTICS

### Sound absorption performance for drapery

There are no technical details for this section.

### Sound absorption performance for upholstery

There are no technical details for this section.

### Sound transmission

There are no technical details for this section.

## WASHABILITY

### Resistance to domestic washing 30° C, indicated in % - ISO 6330

|                             |       |                                       |      |
|-----------------------------|-------|---------------------------------------|------|
| Dimensional change warp     | -0.10 | Dimensional change warp after ironing | 0.20 |
| Dimensional change weft     | -0.07 | Dimensional change weft after ironing | 0.13 |
| Colour fastness ISO 105 C06 | 5     |                                       |      |

### Resistance to domestic washing 40° C, indicated in % - ISO 6330

There are no technical details for this section.

### Resistance to domestic washing 60°C, indicated in % - ISO 6330

|                             |       |                                       |       |
|-----------------------------|-------|---------------------------------------|-------|
| Dimensional change warp     | -0.46 | Dimensional change warp after ironing | 0.46  |
| Dimensional change weft     | -0.40 | Dimensional change weft after ironing | -0.66 |
| Colour fastness ISO 105 C06 | 5     |                                       |       |

### Resistance to domestic washing 74 C ISO 6330

|                             |       |                                       |      |
|-----------------------------|-------|---------------------------------------|------|
| Dimensional change warp     | -0.40 | Dimensional change warp after ironing | 0.00 |
| Dimensional change weft     | -0.90 | Dimensional change weft after ironing | 0.00 |
| Colour fastness ISO 105 C06 | 4     |                                       |      |

### Resistance to dry cleaning P, indicated in % - ISO 105 D01

|                             |       |                                       |      |
|-----------------------------|-------|---------------------------------------|------|
| Dimensional change warp     | -0.23 | Dimensional change warp after ironing | 0.13 |
| Dimensional change weft     | 0.07  | Dimensional change weft after ironing | 0.13 |
| Colour fastness ISO 105 D01 | 5     |                                       |      |

COLLECTION: VELVELUX

DESIGN: VELVELUX

CONSTRUCTION

Yarn 1

|                           |                         |                  |     |
|---------------------------|-------------------------|------------------|-----|
| Warp Composition          | 100% Recycled Polyester | Warp Is Filament | Yes |
| Warp Is Not High Tenacity | Yes                     | Warp Is Staple   | No  |
| Warp Sizes                | 300/96                  | Warp Textured    | Yes |
| Warp Threads per cm       | 22.44                   | Warp TPM         | 0   |

Yarn 2

|                           |                         |                  |     |
|---------------------------|-------------------------|------------------|-----|
| Weft Composition          | 100% Recycled Polyester | Weft Is Filament | Yes |
| Weft Is Not High Tenacity | Yes                     | Weft Is Staple   | No  |
| Weft Sizes                | 150/48                  | Weft Textured    | Yes |
| Weft Threads per cm       | 29.92                   | Weft TPM         | 0   |

DOWNLOADS

-  [Velvelux-FMVSS302](#)
-  [Velvelux-NFPA 260 UFAC](#)
-  [Velvelux - FibreGuard report](#)
-  [Velvelux-Cal 117-2013](#)
-  [Velvelux 24062017A Bru Textiles BS 5852 Source 0](#)

