

Landscape

SpecRite™

Manufactured For Results.



KWILA PRE-OILED SLEEPER

SELECT GRADE HARDWOOD-KILN DRIED-NZS 3602 2003

200 x 50 x 2400

Width (mm)

Thickness (mm)

Length (mm)

- › FSC® 100% kwila hardwood
- › Select grade, kiln dried timber for stability and a high quality, clean appearance
- › Durability class 1 (above ground), class 3 (in ground)
- › Pre-oiled with Feast Watson® Industrial Timber Oil
- › Naturally resistant to fungi and insects like termites and dry woodborers

Warning: Kwila's superior strength and stability are attributable to its tannin-rich properties, resulting in low shrinkage and minimal surface and end splitting. Tannin is a naturally occurring substance in timber which will leach the first few times it is exposed to moisture, staining timber, paved areas and other nearby surfaces. Objects left on the timber surface will also draw tannin out, creating surface marks. A thorough and regular hose down during the first few days will assist in flushing excess tannin away and minimising subsequent staining.

To prolong this product's life and maintain its premium look apply a timber oil containing UV stabiliser within 2 weeks of installation. The surface should be washed and cleaned using a stiff bristle brush then allowed to dry prior to applying a minimum of 2 coats of timber oil.



Item No. 0374401
Made in Indonesia
G/W: 20.4kg