

- > Large shallow water pipelay barge with min. draft of only 3.2 m
- > 300 MT and 73 MT pedestal cranes with man riding capability
- Suitable for flexible and cable lay
- > Accommodation for 260 pax with extensive office and conference facilities











# **Vessel Features**

GENERAL	
Class	ABS +      ABS +
	Work barge/ Crane service/ BWT/
	Helideck/ SPS code 2008 Compliant
Flag	Singapore
Port of Register	Singapore
Year of Built	Nov.2009 (shipyard delivery Oct.2010)
Gross Tonnage	16'111 MT
Net Tonnage	4'833 MT
IMO No.	8357289
Official No./ Call Sign	395633 / 9V8339
Compliances	OVID & ISM: Interim DoC,SMC,ISPS,
	SVOC DMLC
	Director General Shipping, India compliant
	with SPL in place
DIMENSIONS	
LOA	130 m
Breadth	32 m
Depth	8.5 m
Draft (Minimum)	3.2 m
Draft (Maximum)	5.8 m
Draft (Operating)	5.1 m
Deck Loading Cap.	18 MT/m <sup>2</sup> and 15 MT/m <sup>2</sup>
Deck Frame Spacing	0.6 m
Deck Working Space	Approx. 1600 m <sup>2</sup> (1400 m <sup>2</sup> excluding the saturation diving platform)
<b>MOORING SYSTE</b>	VI
Arrangement	8 point mooring system
Mooring Winches	8 x single drum electric VFD drive, 70 MT
5	(mid drum) capacity, complete with 1500 m
	of 52 mm diameter wire ropes
	Make: PH Hydraulics & Engineering
	Model: 110Ton
Winch Control	Local and remote control
System	Fully integrated with pipelay system
Tension Monitoring	Fully automatic with payout length and
System	tension measurement
Anchors	8 x 8 MT Stevpris + 1x 8 MT spare Stevpris
	+ 1x spare 10 MT Delta Flipper
<b>CRANEAGE / LIFT</b>	
Main Crane	Huisman pedestal type rated at 300 MT
	(Sr. No. A08-53000)
Auxiliary Crane	Techcrane pedestal type rated at 73 MT
-	(Model No. F200-100)
Pipe Handling Davits	4 x 50 MT hydraulic luffing type - fully
(Port Side)	centralized remote (control tower) and local
	control
INTEGRITY ACC	

# Leighton Eclipse

Tensioner	2 x 60 MT track tensioners at 25 m/min
Pipe Size Range	6" - 60" overall OD
Control System	Electro hydraulic with manual override joystick
	control, pay in and pay out
Work Stations	Total 8 stations including: 4 x weld stations,
	2 x NDT / repair stations, and 2 x field joint
	stations
Welding System	Accommodates manual, semi-automatic and
	fully automatic
Abandonment	120 MT capacity single drum complete with 810
and Recovery	m of 64 mm diameter wire rope
Winch with Auto	
Load Transfer	
Pipe Handling	Hydraulic system including 2 units transfer
System	chain conveyors, line up and transfer modules
	and elevating rollers
Stinger	Fixed type 40 m long, extendable with 20 m
	floating section
Stinger Winches	2 x 30 MT @ mid layer

#### **ACCOMODATION & HELICOPTER FACILITIES**

Accommodation	Fully air-conditioned & furnished 260 Persons. (10 x 1 man, 27 x 2 man, 49 x 4 man cabins)
Helideck	Suitable for helicopter sizes Sikorsky S61 to S92; equipped with foam system, CAP437 9 <sup>th</sup> Edition compliance
Galley	Fully-equipped to cater 300 man, with cool room, freezer room, and dry store
Common Facilities	Fully-equipped & furnished gymnasium Recreation & cinema Laundry Phone room and internet room Common toilets Change room and locker room Stores
Control Room & Offices	10 dedicated offices IT/Server room Radio cum fully integrated control room Conference room Multi-purpose room
HVAC	Improved indoor air quality with UV-C light germicidal irradiator, sanitizing and destroying, bacteria, mold fungi, and virus
Workshop	Fully equipped mechanical, electrical, welding and common workshops









## **Vessel Features**

MACHINERY	
Generators	7 x 1'040 kW Cummins KTA 50 DM1 - considerable additional genset capacity for positive future crane upgrade up to 900 MT Producing 3 phase 50Hz
Emergency Generator	Caterpillar 3412 DITA 500 kW
Air Compressors	2 x 475 cfm @ 10 bar (service air) 2 x 37 cfm @ 35 bar (line-up clamp) 1 x 102 cfm @ 10 bar (tensioner bags)

SERVICE TANKS	
Marine Diesel Storage	1'363 m <sup>3</sup> @ 98%
Fresh Water Storage	1'177 m <sup>3</sup> @ 100%
Ballast Water	11'078 m <sup>3</sup> , fully ballastable
Sewage Storage	91 m <sup>3</sup>

AUXILIARY EQUIP	AUXILIARY EQUIPMENTS AND PUMPS	
Sewerage Treatment Plant	1 no Hamworthy model ST20 - 300 man capacity with pre-treatment macerator pumps, improved efficiency and additional UV-C light treatment reducing bacteria and E. Coli in the outflow	
Water Maker	2 no x 50 m <sup>3</sup> /day seawater RO desalination plant with UV disinfection system	
Bilge / Fire / Ballast Pump	2 x 150 m³/hr @ 80 m	
Ballast Pump	2 x 300 m³/hr @ 30 m	
Ballast Water Treatment System	1x Tech-Cross Electro-Cleen System ECS300B	
Machinery cooling / GS	2 x 200 m³/hr @ 30 m	
Fuel Oil Cargo Pump	1 x 150 m³/hr @ 50 m	
FW Cargo Pump	1 x 50 m³/hr @ 50 m	
FW Domestic Pump	2 x 20 m³/hr @ 50 m	
SW Domestic Pump	2 x 20 m³/hr @ 50 m	
Sewage Discharge Pump	1 x 15 m³/hr @ 30 m	
Sludge / Dirty Oil Discharge Pump	1 x 5 m³/hr @ 20 m	
FO Transfer Pump	1 x 5 m³/hr @ 30 m	
Lube Oil Transfer Pump	1 x 5 m³/hr @ 20 m	
Hydraulic Oil Transfer Pump	1 x 2 m³/hr @ 20 m	
Hot Water Circulating	2 x 15 m³/hr @ 30 m	

# Leighton Eclipse

#### **COMMUNICATION & NAVIGATION**

Communication System	2 – GMDSS MF / HF radio VHF DSC radio Inmarsat, Mini Sat-C Explosion proof IS portable VHF radio Aviation fixed & Portable transceiver Non-direction radio beacon SSAS EPIRB SART Distress safety system area KU band satellite system CCTV system Satellite TV antenna PA system & talkback system Integrated telephone system Sound powered telephone system LAN System
Navigation System	Radar, Koden MDC 7912P GPS positioning Navtex AIS Compass Weather stations Searchlight, inclinometer and daylight Navigation lights Signaling lamp Fog horn / air horn


### SAFETY EQUIPMENT

Life Boats	2 x 130 person (SOLAS compliant, ABS class) with suitable gravity luffing type davits
Rescue Boats	2 x 40 HP rescue boats each suitable for 6
	persons fitted with suitable davits
Navigation	COLREGS compliant arrangement
Life Rafts	23 x 25 person (SOLAS compliant)
Immersion Suit	264 (25x M, 167x L, 60x XL,12x Adult
	1.5to1.9m)
LifeJacket &Buoy	461x Life Jacket & 24x Buoy
Fire Detection,	Fire detection & alarm system
Alarm & Fighting	Water mist & sprinkler system
	Fire hydrants
	Portable & Non-Portable fire extinguishers
	CO <sub>2</sub> system
	Helideck foam system pump, flow 160 m <sup>3</sup> /hr
	@ 80 m
	Emergency fire fight pump, capacity 50 m <sup>3</sup> /hr
	@ 120 m
CAEETV	


SAFETY

### **Technical Drawing**

### Leighton Eclipse



STBD PROFILE



\* The information provided in this brochure is for general information purposes only and is not intended or to be construed as a warranty, an offer, or any representation of contractual or other legal responsibility. The information is subjected to change without prior notice.

INTEGRITY ACCOUNTABILITY INNOVATION DELIVERY SAFETY

- > Solid pipe and flexible lay track records
- > Min. vessel draft of 3.2 m only
- Record production of approx. 3.8 km/day (308 pipe joints welds in a day)



> 300 MT Huisman crane

Large deck area

 $\succ$  Accommodation for 260 pax with a helideck



> Well suited for platform hook-up support works and riser stalk-on