


# Declaration of performance

No. HHDE 8 0901

Unique identification code of the product-type H + H Blokfix			
Intended use		Designed thin layer masonry mortar (T) applied in thin layers for internal and external applications	
Manufacturer:		LIP Bygningsartikler A/S, Industrivej 16, 5580 Nr. Åby, Danmark	
System of AVCP:		2+	
Harmonized standard:		EN 998-2:2016	
Notified body		NB 1073	
Declared performance			
Compressive strength		NPD	
Bond strength, on aircrete density 375		≥0,3 N/mm²	
Bond strength, on aircrete density 535		≥0,4 N/mm²	
Flexural strength, on aircrete density 375, f <sub>xk1</sub>		0,35 MPa	
Flexural strength, on aircrete density 375, f <sub>xk2</sub>		0,20 MPa	
Flexural strength, on aircrete density 535, f <sub>xk1</sub>		0,50 MPa	
Flexural strength, on aircrete density 535, f <sub>xk2</sub>		0,45 MPa	
Reaction to fire		Class A1	
Contents of chlorides		NPD	
Water absorption		NPD	
Water vapour permeability		NPD	
Thermal conductivity/Density		NPD	
Durability		NPD	
Dangerous substances		NPD	
The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.			
Signed for and on behalf of the manufacturer by:			
Name	Kristian K. Mortensen	Date	25-08-2017
Signature		Place	Nr. Åby