

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

H+H Elementfix Supercedes date 06-Nov-2024 Revision date 12-Dec-2024 Revision Number 2.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name H+H Elementfix

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

H+H Nordics A/S Skanderborgvej 234 8260 Viby J Denmark

Tel: +45 70240050

E-mail address teknik@hplush.dk

1.4. Emergency telephone number

Emergency Telephone 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin irritation	Category 2 - (H315)
Serious eye damage	Category 1 - (H318)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Category 3 Target organ effects: Respiratory irritation.	

2.2. Label elements

Contains Cement, portland, chemicals (Chromium VI reduced); Flue dust, Cement Portland; Calcium diformate



Europe - BE Page 1 / 14

H+H Elementfix
Supercedes date 06-Nov-2024

Revision date 12-Dec-2024 Revision Number 2.01

Signal word

Danger

Hazard statements

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves, eye protection and face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P501 - Dispose of contents/containers in accordance with local regulations

2.3. Other hazards

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

PBT & vPvB

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight- %	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	concentration		M-Factor (long-ter m)	Notes
Quartz 14808-60-7	40 - <80	[5]	238-878-4	[B]	-	-	-	ı
Cement, portland, chemicals (Chromium VI reduced) 65997-15-1	40 - <80	[5]	266-043-4	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT SE 3 (H335)		-	-	-
Flue dust, Cement Portland 68475-76-3	1 - <2.5	01-2119486767 -17-XXXX	270-659-9	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT SE 3 (H335)		-	-	1
Calcium diformate 544-17-2	1 - <2.5	01-2119486476 -24-XXXX	208-863-7	Eye Dam. 1 (H318)	-	-	-	-

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

Europe - BE Page 2 / 14

H+H Elementfix
Supercedes date 06-Nov-2024

Revision date 12-Dec-2024 Revision Number 2.01

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	
Quartz	238-878-4	14808-60-7	-	-	-	-	-
Cement, portland, chemicals (Chromium VI reduced)	266-043-4	65997-15-1	-	-	-	-	-
Flue dust, Cement Portland	270-659-9	68475-76-3	-	-	-	-	-
Calcium diformate	208-863-7	544-17-2	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Take a copy of the

Safety Data Sheet when going for medical treatment.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or

concerned: Get medical advice/attention.

Eye contact Do not rub affected area. Immediately flush with plenty of water. After initial flushing,

remove any contact lenses and continue flushing for at least 15 minutes. Consult an

ophthalmologist.

Skin contact Brush off loose particles from skin. Remove material from skin immediately. Take off

contaminated clothing and wash it before reuse.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Dust irritates eyes and air passages. Causes serious eye damage.

Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g.

Europe - BE Page 3 / 14

H+H Elementfix Supercedes date 06-Nov-2024 Revision date 12-Dec-2024 **Revision Number** 2.01

when kneeling in wet cement even when wearing trousers.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Full water jet. Do not scatter spilled material with high pressure water streams. Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

No information available.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal

protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry.

Prevent dust cloud.

Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect Methods for cleaning up

dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep

up spilled material and place in suitable container. Avoid generating dust.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Page 4 / 14 Europe - BE

H+H Elementfix
Supercedes date 06-Nov-2024

Revision date 12-Dec-2024 Revision Number 2.01

Advice on safe handling Ensure adequate ventilation. Avoid generation of dust. Use personal protection

equipment. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children. Keep the packing dry and well sealed to prevent

contamination and absorption of humidity. Protect from moisture.

7.3. Specific end use(s)

Specific use(s)

Adhesive.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Quartz	TWA: 0.1 mg/m ³
14808-60-7	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DN	EL)		
Quartz (14808-60-7)			
Calcium diformate (544-17-2			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker	Inhalation	337 mg/m ³	
Short term			
Systemic health effects			
worker	Inhalation	337 mg/m ³	
Long term			
Systemic health effects			
worker	Dermal	16.7	
Short term			
Local health effects			
worker	Dermal	4780 mg/kg bw/d	
Short term			
Systemic health effects			
worker	Dermal	16.7 mg/cm ²	
Long term			
Local health effects			
worker	Dermal	4780 mg/kg bw/d	
Long term			
Systemic health effects			

Europe - BE Page 5 / 14

H+H Elementfix Supercedes date 06-Nov-2024 Revision date 12-Dec-2024 Revision Number 2.01

Derived No Effect Level (DNEI	Derived No Effect Level (DNEL)						
Calcium diformate (544-17-2)							
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor				
Consumer Long term Systemic health effects	Oral	23.9 mg/kg bw/d					
Consumer Short term Local health effects	Dermal	8.3 mg/cm ²					
Consumer Short term Systemic health effects	Dermal	2390 mg/kg bw/d					
Consumer Long term Local health effects	Dermal	8.3 mg/cm ²					
Consumer Long term Systemic health effects	Dermal	2390 mg/kg bw/d					
Consumer Short term Systemic health effects	Inhalation	83.2 mg/m³					
Consumer Long term Systemic health effects	Inhalation	83.2 mg/m³					

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)					
Calcium diformate (544-17-2)					
Environmental compartment	Predicted No Effect Concentration (PNEC)				
Freshwater	2 mg/l				
Freshwater - intermittent	10				
Freshwater sediment	13.4 mg/kg dry weight				
Marine water	0.2				
Marine sediment	1.34				

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Gloves made of plastic or rubber. Gloves should be replaced regularly and if there is any

sign of damage to the glove material. Gloves must conform to standard EN 374.

Skin and body protection Suitable protective clothing.

Respiratory protection None under normal use conditions. In case of inadequate ventilation wear respiratory

protection.

Recommended filter type: Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid Appearance Powder

Europe - BE Page 6 / 14

H+H Elementfix Supercedes date 06-Nov-2024 Revision date 12-Dec-2024 Revision Number 2.01

ColourGrey WhiteOdourOdourless.

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing point Not applicable . None known Initial boiling point and boiling Not applicable . None known

Initial boiling point and boiling Not applicable . None know range

Flammability No data available None known

Flammability Limit in Air None known

Upper flammability or explosive No data available **limits**

Lower flammability or explosive No data available

limits

Flash point Not applicable . None known Autoignition temperature No data available None known Decomposition temperature No data available None known None known

pHNo data availableNone known.pH (as aqueous solution)11 - 13None knownKinematic viscosityNot applicable .None knownDynamic viscosityNot applicable .

Water solubility Miscible in water. Cement based None known

products react and solidify in contact

with water

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVapour pressureNo data availableNone knownRelative densityNo data availableNone known

Relative density

Bulk density

Liquid Density

No data available

No data available

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

Softening point Not relevant

VOC content No data available

9.2.1. Information with regards to physical hazard classes Not applicable

....

9.2.2. Other safety characteristics No information available Not applicable .

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under recommended storage conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

Europe - BE Page 7 / 14

H+H Elementfix Supercedes date 06-Nov-2024 Revision date 12-Dec-2024 Revision Number 2.01

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Acids. Aluminium.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation.

(based on components).

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapour) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	>2000 mg/kg (Rattus)	-	-
Cement, portland, chemicals (Chromium VI reduced)	-	>2000 Kg/mg (Lapin)	>5 g/m³ (Rattus)
Flue dust, Cement Portland	-	LD5 >= 2000 mg/kg (Rat) OECD 402	> 6.04 mg/L (Rat) 4 h

Europe - BE Page 8 / 14

H+H Elementfix
Supercedes date 06-Nov-2024

Revision date 12-Dec-2024 Revision Number 2.01

Calcium diformate	=2650 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	-
		OECD 402	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Calcium diformate	RC50 (72h) >	LC50:	-	EC50 (48h) >		
544-17-2	1000 mg/l	>=1000mg/L		1000 mg/l		
	(Pseudokirchner	(96h,		(Daphnia		
	ella subcapitata)	Brachydanio		magna)		
		rerio)		EPA-660/3-75-0		
				09		

12.2. Persistence and degradability

Europe - BE Page 9 / 14

H+H Elementfix
Supercedes date 06-Nov-2024

Revision date 12-Dec-2024 Revision Number 2.01

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

Chemical name	PBT and vPvB assessment
Flue dust, Cement Portland	PBT assessment does not apply
Calcium diformate	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 16 03 03* inorganic wastes containing hazardous substances

17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09

01, 17 09 02 and 17 09 03

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

<u>IMDG</u>

14.1 UN number or ID number
Not regulated
Not regulated
Not regulated

Europe - BE Page 10 / 14

H+H Elementfix
Supercedes date 06-Nov-2024

Revision date 12-Dec-2024 Revision Number 2.01

14.3 Transport hazard class(es) Not regulated14.4 Packing group Not regulated

14.5 Marine pollutant NP
14.6 Special precautions for user
Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user Special Provisions None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH
		Annex XVII
Cement, portland, chemicals (Chromium VI reduced)	65997-15-1	Use restricted. See entry 47.

47 where product supplied with reducing agent the packaging must be marked with the storage conditions and storage period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) Regulation (EU) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

Europe - BE Page 11 / 14

H+H Elementfix
Supercedes date 06-Nov-2024

Revision date 12-Dec-2024 Revision Number 2.01

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Quartz	RG 25
14808-60-7	
Cement, portland, chemicals (Chromium VI reduced)	RG 8,RG 10
65997-15-1	

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

TRGS - 510 Storage Class Storage Class 13 : Non-combustible solids

TA Luft (German Air Pollution Control Regulation)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands - List of Carcinogens
Quartz	Present (respirable dust, crystalline)
14808-60-7	

Sweden

Occupational exposure limits AFS 2018:1

Swedish Work Environment Authority's Statute (AFS 2015:2) QUARTZ AFS 2015:2

Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product. AFS 2012:3

Denmark

Registration number(s) (P-no.) 4575814 **MAL-Code** 00-4

Young people under the age of 18 may not professionally use or be exposed to the product. However, young people over the age of 15 are exempt from this rule if the product is included as a necessary part of an education

AT-Guide C.0.1 August 2007: Limit values for substances and materials

Norway

Registration number(s) (PRN-no.) 637322

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

Europe - BE Page 12 / 14

H+H Elementfix
Supercedes date 06-Nov-2024

Revision date 12-Dec-2024 Revision Number 2.01

H315 - Causes skin irritation

H318 - Causes serious eye damage H335 - May cause respiratory irritation

SVHC: Substances of Very High Concern for Authorisation:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
AGW Occupational exposure limit value BGW Biological limit value
Ceiling Maximum limit value Sk* Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme

Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 12-Dec-2024

Training Advice No information available

Europe - BE Page 13 / 14

H+H Elementfix
Supercedes date 06-Nov-2024

Revision date 12-Dec-2024 Revision Number 2.01

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Europe - BE Page 14 / 14