

## DECLARATION OF PERFORMANCE

**No. HHSEPL 2.1-2,5-375**

1. Unique identification code of the product-type:  
**Celblocket 375 / 599x250x199**  
**Article number: 20252060**
  
2. Intended use:  
**In masonry walls, columns and partitions.**
  
3. Manufacturer:  
**H+H Polska Sp. z o. o.**  
**ul. Bonifraterska 17**  
**00-203 Warszawa**
  
4. System or systems of assessment and verification of constancy of performance:  
**System 2+**
  
5. Harmonized standard:  
**EN-771-4:2011+A1:2015**

The notified factory production control body:

**Institute of Ceramics and Building Materials, Department of Certification, Notified Body Nr: 1487**

6. Declared performance:

Essential Characteristics	Performance	
Dimensions and dimensional tolerances	Length	599 mm
	Width	250 mm
	Height	199 mm
	Dimensional tolerances	TLMB
	Length	+/- 1,5 mm
	Width	+/- 1,5 mm
	Height	+/- 1,0 mm
	Flatness of bed faces	≤ 1,0 mm
	Plane parallelism of bed faces	≤ 1,0 mm
Configuration	Solid with gripholes (according to EN 1996-1-1)	Group 1
Compressive strength	Compressive strength unit category	I
	Mean compressive strength (⊥ bedface) [ $f_b$ ]	≥ 2,5 N/mm <sup>2</sup>
	Type of sample	100 mm x 100 mm x 100 mm
Dimensional stability	Moisture movement [ $\epsilon_{cs}$ , ref.]	≤ 0,2 mm/m

Bond strength	Shear bond strength for thin layer mortar [ $f_{vk0}$ ]	$\geq 0,3 \text{ N/mm}^2$ (Fixed value according to EN 998-2)
	Flexural bond strength in the plane of failure parallel to the bed joints [ $f_{xk1}$ ]	NPD
	Flexural bond strength in the plane of failure perpendicular to the bed joints [ $f_{xk2}$ ]	NPD
Reaction to fire	Euroclass A1	
Water absorption	NPD	
Water vapour diffusion coefficient [ $\mu$ ]	5/10	
Direct airborne sound insulation	Declared dry gross density	375 +/-25kg/m <sup>3</sup>
	Configuration	As above
	Dimensions and dimensional tolerances	As above
Durability against freeze-thaw	Durability	NPD
Thermal resistance	[ $\lambda_{10,dry} (P=50\%)$ ]	$\leq 0,096 \text{ W/(m K)}$
Dangerous substances	None	

7. The performance of the product correspond to the declared performance.

This declaration of performance was issued according to (UE) no. 305/2011 under the sole responsibility of the manufacturer specified in paragraph 3.

Signed on behalf of the manufacturer by:

**Warsaw 07.01.2026**

(place and date of issue)

**Piotr Lokumski**

(Name and Surname)

**H+H POLSKA Sp. z o.o.**  
ul. Bonifraterska 17, 00-203 Warszawa  
*Piotr Lokumski*  
Menedżer ds. Technologii i Jakości  
Pełnomocnik Zarządu ds. ZKP  
NIP 526-28-51-983 REGON 140101184

.....  
(signature)

**Wojciech Zdziechowski**

(Name and Surname)

**H+H POLSKA Sp. z o.o.**  
*Wojciech Zdziechowski*  
Dyrektor ds. Operacyjnych  
Członek Zarządu  
ul. Bonifraterska 17, 00-203 Warszawa  
NIP PL5262851983, REGON 140101184

.....  
(signature)

## DECLARATION OF PERFORMANCE

No. HHSEPL 2.2-2,5-375

1. Unique identification code of the product-type:  
**Celblocket 375 / 599x300x199**  
**Article number: 20302060**
2. Intended use:  
**In masonry walls, columns and partitions.**
3. Manufacturer:  
**H+H Polska Sp. z o. o.**  
**ul. Bonifraterska 17**  
**00-203 Warszawa**
4. System or systems of assessment and verification of constancy of performance:  
**System 2+**
5. Harmonized standard:  
**EN-771-4:2011+A1:2015**

The notified factory production control body:

**Institute of Ceramics and Building Materials, Department of Certification, Notified Body Nr: 1487**

6. Declared performance:

Essential Characteristics	Performance	
Dimensions and dimensional tolerances	Length	599 mm
	Width	300 mm
	Height	199 mm
	Dimensional tolerances	TLMB
	Length	+/- 1,5 mm
	Width	+/- 1,5 mm
	Height	+/- 1,0 mm
	Flatness of bed faces	≤ 1,0 mm
	Plane parallelism of bed faces	≤ 1,0 mm
Configuration	Solid with gripholes (according to EN 1996-1-1)	Group 1
Compressive strength	Compressive strength unit category	I
	Mean compressive strength (⊥ bedface) [ $f_b$ ]	≥ 2,5 N/mm <sup>2</sup>
	Type of sample	100 mm x 100 mm x 100 mm
Dimensional stability	Moisture movement [ $\epsilon_{cs}$ , ref.]	≤ 0,2 mm/m

Bond strength	Shear bond strength for thin layer mortar [ $f_{vk0}$ ]	$\geq 0,3 \text{ N/mm}^2$ (Fixed value according to EN 998-2)
	Flexural bond strength in the plane of failure parallel to the bed joints [ $f_{xk1}$ ]	NPD
	Flexural bond strength in the plane of failure perpendicular to the bed joints [ $f_{xk2}$ ]	NPD
Reaction to fire	Euroclass A1	
Water absorption	NPD	
Water vapour diffusion coefficient [ $\mu$ ]	5/10	
Direct airborne sound insulation	Declared dry gross density	375 +/-25kg/m <sup>3</sup>
	Configuration	As above
	Dimensions and dimensional tolerances	As above
Durability against freeze-thaw	Durability	NPD
Thermal resistance	$[\lambda_{10,dry} (P=50\%)]$	$\leq 0,096 \text{ W/(m K)}$
Dangerous substances	None	

7. The performance of the product correspond to the declared performance.

This declaration of performance was issued according to (UE) no. 305/2011 under the sole responsibility of the manufacturer specified in paragraph 3.

Signed on behalf of the manufacturer by:

**Warsaw 07.01.2026**

(place and date of issue)

**Piotr Lokumski**

(Name and Surname)

**H+H POLSKA Sp. z o.o.**  
ul. Bonifraterska 17, 00-203 Warszawa  
*Piotr Lokumski*  
Menedżer ds. Technologii i Jakości  
Pełnomocnik Zarządu ds. ZKP  
NIP 526-28-51-983 REGON 140101184

.....  
(signature)

**Wojciech Zdziechowski**

(Name and Surname)

**H+H POLSKA Sp. z o.o.**  
*Wojciech Zdziechowski*  
Dyrektor ds. Operacyjnych  
Członek Zarządu  
ul. Bonifraterska 17, 00-203 Warszawa  
NIP PL 5262851983, REGON 140101184

.....  
(signature)

## DECLARATION OF PERFORMANCE

No. HHSEPL 2.3-2,5-375

1. Unique identification code of the product-type:  
**Celblocket 375 / 499x365x99**  
**Article number: 20361050**
2. Intended use:  
**In masonry walls, columns and partitions.**
3. Manufacturer:  
**H+H Polska Sp. z o. o.**  
**ul. Bonifraterska 17**  
**00-203 Warszawa**
4. System or systems of assessment and verification of constancy of performance:  
**System 2+**
5. Harmonized standard:  
**EN-771-4:2011+A1:2015**

The notified factory production control body:

**Institute of Ceramics and Building Materials, Department of Certification, Notified Body Nr: 1487**

6. Declared performance:

Essential Characteristics	Performance	
Dimensions and dimensional tolerances	Length	499 mm
	Width	365 mm
	Height	99 mm
	Dimensional tolerances	TLMB
	Length	+/- 1,5 mm
	Width	+/- 1,5 mm
	Height	+/- 1,0 mm
	Flatness of bed faces	≤ 1,0 mm
	Plane parallelism of bed faces	≤ 1,0 mm
Configuration	Solid with gripholes (according to EN 1996-1-1)	Group 1
Compressive strength	Compressive strength unit category	I
	Mean compressive strength (⊥ bedface) [ $f_b$ ]	≥ 2,5 N/mm <sup>2</sup>
	Type of sample	100 mm x 100 mm x 100 mm
Dimensional stability	Moisture movement [ $\epsilon_{cs}$ , ref.]	≤ 0,2 mm/m

Bond strength	Shear bond strength for thin layer mortar [ $f_{vk0}$ ]	$\geq 0,3 \text{ N/mm}^2$ (Fixed value according to EN 998-2)
	Flexural bond strength in the plane of failure parallel to the bed joints [ $f_{xk1}$ ]	NPD
	Flexural bond strength in the plane of failure perpendicular to the bed joints [ $f_{xk2}$ ]	NPD
Reaction to fire	Euroclass A1	
Water absorption	NPD	
Water vapour diffusion coefficient [ $\mu$ ]	5/10	
Direct airborne sound insulation	Declared dry gross density	375 +/-25kg/m <sup>3</sup>
	Configuration	As above
	Dimensions and dimensional tolerances	As above
Durability against freeze-thaw	Durability	NPD
Thermal resistance	$[\lambda_{10,dry} (P=50\%)]$	$\leq 0,096 \text{ W/(m K)}$
Dangerous substances	None	

7. The performance of the product correspond to the declared performance.

This declaration of performance was issued according to (UE) no. 305/2011 under the sole responsibility of the manufacturer specified in paragraph 3.

Signed on behalf of the manufacturer by:

**Warsaw 07.01.2026**

(place and date of issue)

**Piotr Lokumski**

(Name and Surname)

**H+H POLSKA Sp. z o.o.**  
ul. Bonifraterska 17, 00-203 Warszawa  
*Piotr Lokumski*  
Menedżer ds. Technologii i Jakości  
Pełnomocnik Zarządu ds. ZKP  
NIP 526-28-51-983 REGON 140101184

.....  
(signature)

**Wojciech Zdziechowski**

(Name and Surname)

**H+H POLSKA Sp. z o.o.**  
*Wojciech Zdziechowski*  
Dyrektor ds. Operacyjnych  
Członek Zarządu  
ul. Bonifraterska 17, 00-203 Warszawa  
NIP PL 5262851983, REGON 140101184

.....  
(signature)

## DECLARATION OF PERFORMANCE

No. HHSEPL 2.4-2,5-375

1. Unique identification code of the product-type:  
**Celblocket 375 / 499x365x199**  
**Article number: 20362050**
2. Intended use:  
**In masonry walls, columns and partitions.**
3. Manufacturer:  
**H+H Polska Sp. z o. o.**  
**ul. Bonifraterska 17**  
**00-203 Warszawa**
4. System or systems of assessment and verification of constancy of performance:  
**System 2+**
5. Harmonized standard:  
**EN-771-4:2011+A1:2015**

The notified factory production control body:

**Institute of Ceramics and Building Materials, Department of Certification, Notified Body Nr: 1487**

6. Declared performance:

Essential Characteristics	Performance	
Dimensions and dimensional tolerances	Length	499 mm
	Width	365 mm
	Height	199 mm
	Dimensional tolerances	TLMB
	Length	+/- 1,5 mm
	Width	+/- 1,5 mm
	Height	+/- 1,0 mm
	Flatness of bed faces	≤ 1,0 mm
	Plane parallelism of bed faces	≤ 1,0 mm
Configuration	Solid with gripholes (according to EN 1996-1-1)	Group 1
Compressive strength	Compressive strength unit category	I
	Mean compressive strength ( $\perp$ bedface) [ $f_b$ ]	≥ 2,5 N/mm <sup>2</sup>
	Type of sample	100 mm x 100 mm x 100 mm
Dimensional stability	Moisture movement [ $\epsilon$ cs, ref.]	≤ 0,2 mm/m

Bond strength	Shear bond strength for thin layer mortar [ $f_{vk0}$ ]	$\geq 0,3 \text{ N/mm}^2$ (Fixed value according to EN 998-2)
	Flexural bond strength in the plane of failure parallel to the bed joints [ $f_{xk1}$ ]	NPD
	Flexural bond strength in the plane of failure perpendicular to the bed joints [ $f_{xk2}$ ]	NPD
Reaction to fire	Euroclass A1	
Water absorption	NPD	
Water vapour diffusion coefficient [ $\mu$ ]	5/10	
Direct airborne sound insulation	Declared dry gross density	375 +/-25kg/m <sup>3</sup>
	Configuration	As above
	Dimensions and dimensional tolerances	As above
Durability against freeze-thaw	Durability	NPD
Thermal resistance	$[\lambda_{10,dry} (P=50\%)]$	$\leq 0,096 \text{ W/(m K)}$
Dangerous substances	None	

7. The performance of the product correspond to the declared performance.

This declaration of performance was issued according to (UE) no. 305/2011 under the sole responsibility of the manufacturer specified in paragraph 3.

Signed on behalf of the manufacturer by:

**Warsaw 07.01.2026**

(place and date of issue)

**Piotr Lokumski**

(Name and Surname)

**H+H POLSKA Sp. z o.o.**  
ul. Bonifraterska 17, 00-203 Warszawa  
*Piotr Lokumski*  
Menedżer ds. Technologii i Jakości  
Pełnomocnik Zarządu ds. ZKP  
NIP 526-28-51-983 REGON 140101184

.....  
(signature)

**Wojciech Zdziechowski**

(Name and Surname)

**H+H POLSKA Sp. z o.o.**  
*Wojciech Zdziechowski*  
Dyrektor ds. Operacyjnych  
Członek Zarządu  
ul. Bonifraterska 17, 00-203 Warszawa  
NIP PL 5262851983, REGON 140101184

.....  
(signature)