

CROZIER

Standard Crate



Ideal For

Professional level construction with economical materials.

Design

Every build custom designed in alignment with exacting standards. Asset consolidation for sustainability.

Modification

Further customizable at the component level.

Reuse

Yes.

Access

Loading oriented for best access. Options include one lid, multiple lids, or all walls removable.

Closures

Steel screws. Bolt plates available upon request.

Vapor Barrier Lining

Available upon request.

Interior Bracing

Lumber & A-C plywood as needed.

Exterior Finish

Rounded edges, screw holes filled, all sanded. Paint or clear water-based lacquer exterior seal.

Exterior Marks

Lid registration, up-arrows, "fragile", piece number, unique serial number, dimensions, weight, ISPM 15 "bug stamp".

Wall Material

1/2" A-C grade plywood.

Reinforcements

Fully battened with 3/4" pine lumber. Corner battens to reinforce joins.

Skids

Solid wood, 3.5" tall. Patterned for four-way handling access whenever possible.

Handles

Solid wood, consistent height for safe lifting.

Insulation

Available upon request.

Cushioning

2" minimum of high-grade foam all around. Calculated to target the optimal static load case-by-case.

Interior Packaging

A-C plywood, 1/2" foam board, 1/2" honeycomb, or double-wall cardboard for interior boxes and panels.

Documentation

Pack list, packing instructions as needed, carbon estimate, and fully detailed specs kept on file.

TSA Screening

Available upon request or regulation.

[Consult a Crating Expert](#)