

Troubleshooting high bacteria counts in farm milk

General Information

Operator _____

Phone _____ Date _____

Address _____

Equipment Dealer _____

Phone _____

Chemical Supplier _____

Phone _____

Prioritized Recommendations


1. _____

2. _____

3. _____

4. _____

System Sketch




Part 1a

Routine Milk Quality Analysis

Bulk tank cultures can be used to diagnose equipment cleaning and sanitation problems, incubation of bacteria in the milk handling system during milking, inadequate pre-milking hygiene, and mastitis. Here is a list of goals and action levels for each type of test.

- Equipment cleaning and sanitation problems generally result in elevated LPC counts.
- Incubation of bacteria in the milking system cause elevated Coli (above 1000) and LPC counts.
- Inadequate premilking hygiene will result in elevated Coli counts (typically 100 to 1000) .
- If both SCC and SPC are high mastitis organisms may be the cause of high bacteria counts.



Composite milk samples should be taken from the bulk tank at the time the milk is shipped from the farm. The tests indicated above should be performed on a routine basis a minimum of monthly on small farms and weekly on large farms and more often if a problem situation exists. A minimum of three tests is needed to make a diagnosis. Record the culture results and test dates below:

Dates						
SPC: Standard Plate Count						
LPC: Lab Pasteurized Count						
Coli: Coliform Count						
SCC: Somatic Cell Count						



Part 1b

Strategic Sampling

If routine bulk tank analysis indicates that equipment cleaning and sanitation may be a problem it is desirable to further diagnose the source of the problem. Milk samples should be taken from the receiver(s), transfer line(s) and bulk tank after the first group of cows is milked (one cow for each milking unit) and after every 4 hours of milking (or since the system has been washed) with a final sample taken at the end of milking (or before the next wash cycle). Record the results of these tests in the following table.

SPC	After first group of cows	After 4 Hours	After 8 Hours	End of Milking
Time of Sample				
Receiver 1				
Receiver 2				
Transfer Line 1				
Transfer Line 2				
Bulk Tank 1				
Bulk Tank 2				

- Elevated counts in the receiver samples at the beginning of milking likely indicates a cleaning problem in the milking units, milk meters, milkline or hoses. If this situation exists perform the CIP flow analysis.
- Elevated counts in transfer lines but not in receiver after the first group of cows indicates cleaning failure in the transfer line and equipment between the receiver and bulk tank such as plate coolers and milk filters.
- A continual rise in counts during milking indicates incubation as the likely cause. Solutions to this problem may include washing the system more thoroughly and frequently or changing the milk filter more frequently.



Part 2a

CIP Procedures Observations

- Yes No** Does the sanitary trap valve close (trapout) during the CIP procedure?
- Yes No** Is air drawn into units or wash lines at the wash sink?
- Yes No** Is the ball removed from the sanitary trap during washing?
- Yes No** Does more than 5 gallons of water drain from the balance tank after the wash cycle?
- Yes No** Does the milk pump run continuously during the wash cycle?
- Yes No** Is there any visible residue on system components?

Describe:

Location	Color	Texture	Acid Solution	Detergent Soluable	Chlorine Soluable

- Yes No** Is the system “shock” treated? **If yes**, how often? (note shock treatment dates on bulk tank culture records)

- Yes No** Do any system components fail to drain after CIP procedure? **If yes**, note which?

- Yes No** Are any valves actuated manually before or during CIP procedure? **If yes**, note which

Milk Temperature:	Entering bulk tank _____ End of milking _____				
	At pickup: Top of tank _____ Bottom of tank _____				
	Premilking Sanatize	Prewash Rinse	Detergent Wash	Acid Rinse	Other
Start Temp					
Start Temp					
Cycle Time					
Product Used					
Label Concentration					
Label Temp					
Other Measurements (pH, alkalinity, etc.)					
Guidelines	Follow label instructions for time temp, and concentration	110 - 130 F (43-57C)	Follow label Instructions. (6-10 min, 120 F, typical)	Follow label instructions. (2 min, 90-110 F typical)	



Part 3

Water quantity and quality

Water hardness _____

Water iron content _____

Water softener? **Yes No**

Is water softener charged **Yes No**

Other water test results _____

Water Heater	Temp	Capacity
Tank 1		
Tank 2		
Tank 3		
	Wash sink	

Determine the minimum water volume required per wash cycle for proper flow dynamics in air-injected milking systems. Use this estimate to size wash sinks in new systems or to check if the actual water used per cycle is higher or lower than the minimum requirement. The requirement for milk meters, wash vat and precoolers are approximate and may vary with different component designs. If air injection is not used multiply the total gallons for the milkline by 3. If weigh jars are used, multiply the milk meter gallons by 4.

	(x) Multiplier	(=) Gallons
Feet of milkline		
Line diameter 4 in.	x 0.12	=
Line diameter 3 in.	x 0.07	=
Line diameter 2.5 in.	x 0.05	=
Line diameter 2 in.	x 0.03	=
Line diameter 1.5 in.	x 0.02	=
Feet of wash draw and milk transfer line		
Line diameter 3 in.	x 0.34	=
Line diameter 2.5 in.	x 0.23	=
Line diameter 2 in.	x 0.15	=
Line diameter 1.5 in.	x 0.09	=
Receiver(s) Volume (gallons)		
	x 0.33	=
Number of milking units		
	x 0.25	=
Number of milk meters		
	x 0.25	=
Feet of milk hose		
Hose diameter 9/16 in	x 0.012	=
Hose diameter 5/8 in	x 0.012	=
Number of precoolers		
	x 2	=
Number of wash vats		
	x 8	=
Total Gallons		=



Part 5

Milkline Slug Flow Analysis

Estimate Air injector open time		Injector 1	Injector 2
Slug travel distance from air injector through air injector line and milkline to receiver (feet or meters)			
Expected air injector open time: divide slug travel distance by 28 ft/sec (8.5 m/s) or other slug speed (seconds)			
Estimate expected time between vacuum drop at test points		Injector 1	Injector 2
Distance between test points (points at which vacuum recorder attached to milk line) (feet or meters)			
Time between vacuum drops: divide distance between test points by 28 ft/sec (8.5 m/s) or other slug speed (seconds)			

Vacuum Drop and Slug Speed Measurements: Attach vacuum recordings to form

	If Sequenced	Time between vacuum drop at test points	Slug Speed	Vacuum Drop At Test Points
		Loop 1 Loop 2	Loop 1 Loop 2	Loop 1 Point 1 Loop 2 Point 1 Loop 2 Point 2
As Found	Washline injector open			
1st Adjustment				
2nd Adjustment				
3rd Adjustment				
Final Setting				
Guideline	Long enough to form a slug to receiver	Just long enough to move slug to receiver	Adjust air flowrate to change slug speed	4 - 9 in. (12-30) Hg for 3" line 5-7 in Hg. (18-25kPa for 2 in. line)

Vacuum Drop at other locations

Location (refer to sketch)									
Vacuum Drop									

