

A93 Grade 93.0 Premium Unleaded Gasoline Specifications

(This Conventional Before Oxygenate Blending (CBOB) gasoline is intended for blending with 10% Denatured Fuel Ethanol (DFE) by volume).

Product Property	Method	Minimum	Maximum
Gravity, ° API	D287		Report
Color Volatility ^{2/}			Undyed
RVP ^{6/8/}	D5191		
Distillation ^{9/}	D86		
Benzene, vol % ^{9/}	D3606		4.9
Mercaptan Sulfur, wt % ^{3/}	D3227		0.003
Copper Corrosion	D130		1
Silver Corrosion	D7667, 7671		1
Gum, Existent, mg/100 ml	D381		4
Oxidation Stability, minutes	D525	240	
Phosphorus, g/gal	D3231		0.003
Lead, g/gal	D3237		0.010
Octane ^{9/}			
RON	D2699		Report
MON	D2700		Report
(R+M)/2		93.0	
Sulfur, ppm ^{8/}	D2622		80
Oxygenates, vol% ^{7/}	D4815, D5599		0.05
Haze Rating ^{4/}	D4176		2
NACE Corrosion	TM0172, D7548	B+	
Odor ^{5/}		Nonoffensive	

A93 Grade 93.0 Premium Unleaded Gasoline Specifications (continued)

Foot Notes:

- 1/ Delivered products meet all applicable requirements at time and place of delivery.
- 2/ Refer to Magellan's Seasonal Gasoline Volatility Classes and Schedule of Origin Volatility requirements.
- 3/ Mercaptan Sulfur determination is waived if the result of the Doctor Test ASTM D4952 is negative.
- 4/ Compliance with ASTM D4176 will be determined using Procedure 2 at the following temperatures, adjusted seasonally:

February 16 – September 30	55 °F max
October 1– February 15	45 °F max
- 5/ Any gasoline exhibiting an offensive odor and/or containing more than 0.30 wt % dicyclopentadiene will not be accepted for shipment.
- 6/ RVP limits on ethanol blended gasoline are controlled by various federal and state regulations and waivers, which are generally greater than the limits for base gasoline.
- 7/ Values below the detectible limit of an approved method may be reported as a zero value.
- 8/ Values will be reported on the 0 and 10 percent oxygenated gasoline.
- 9/ Value will be reported on the 10 percent oxygenate blend.

Notes:

- All parameters must be met without blending of denatured fuel ethanol unless noted.
- In accordance with 40 CFR 1190.1010(a), gasoline will be accepted when designated as E0 or E10 for oxygenate with ethanol as described by 40 CFR 1090.1110(c)(2). In accordance with 40 CFR 1090.1110(a), gasoline will be designated upon receipt as Winter CBOB or Summer CBOB (7.8 psi, 9.0 psi, or SIP-controlled) based on the RVP of the base gasoline.
- All gasoline distributed will be designated as E10 as described by 40 CFR 1090.1110(c)(2).
- Any product with a 7.8 psi or 9.0 psi CBOB does not meet the requirements for summer reformulated gasoline.
- This product is non-additized gasoline.