

SECTION 1: IDENTIFICATION**1.1. Product Identifier****Product Form:** Mixture**Product Name:** Butane-Isobutane Mix**CAS Number:** 68477-85-0**Synonyms:** Commercial Butane, Mixed Butane, RGB, Refinery Grade, Liquefied Petroleum Gas (LPG)**1.2. Intended Use of the Product****Use of the Substance/Mixture:** Industrial Use**1.3. Name, Address, and Telephone of the Responsible Party****Corporation**

ONEOK, Inc.

100 W. Fifth Street

Tulsa, OK 74103

Tel (888) 417-6275

Fax (918) 588-7543

www.oneok.com**1.4. Emergency Telephone Number****Emergency Number** : For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night within USA and Canada: 1-800-424-9300 or +1 703-527-3887 (collect calls accepted)**SECTION 2: HAZARDS IDENTIFICATION****2.1. Classification of the Substance or Mixture****GHS-US Classification**

Flammable gases Category 1 H220

Gases under pressure Liquefied gas H280

Simple Asphyxiant S1AS

Hazardous to the aquatic environment - Acute Hazard Category 3 H402

Hazardous to the aquatic environment - Chronic Hazard Category 3 H412

2.2. Label Elements**GHS-US Labeling****Hazard Pictograms (GHS-US)****Signal Word (GHS-US)** : Danger**Hazard Statements (GHS-US)**: H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.
H402 - Harmful to aquatic life.
H412 - Harmful to aquatic life with long lasting effects.
May displace oxygen and cause rapid suffocation.**Precautionary Statements (GHS-US)**: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 - Avoid release to the environment.
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 - Eliminate all ignition sources if safe to do so.
P403 - Store in a well-ventilated place.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.**2.3. Other Hazards**

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Contact with gas escaping the container can cause frostbite.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

Butane-Isobutane Mix

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Name : Butane-Isobutane Mix

CAS-No. : 68477-85-0

Name	Synonyms	Product Identifier	%	GHS US classification
n-Butane	Butane / BUTANE	(CAS-No.) 106-97-8	68 – 74	Simple Asphy, SIAS Flam. Gas 1, H220 Press. Gas (Liq.), H280
Isobutane	2-Methylpropane / Propane, 2-methyl- / ISOBUTANE / R600a / isobutane	(CAS-No.) 75-28-5	18 – 30	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Simple Asphy, SIAS
Isopentane	Butane, 2-methyl- / 2-Methylbutane / ISOPENTANE / Methylbutane / isopentane	(CAS-No.) 78-78-4	≤ 6	Flam. Liq. 1, H224 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Propane	Normal propane / PROPANE / n-Propane / R290	(CAS-No.) 74-98-6	≤ 2	Simple Asphy, SIAS Flam. Gas 1, H220 Press. Gas (Liq.), H280
n-Pentane	Pentane / Normal pentane / PENTANE / Pentane, n-	(CAS-No.) 109-66-0	≤ 2	Flam. Liq. 1, H224 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Ethane	Ethyl hydride / ETHANE	(CAS-No.) 74-84-0	≤ 0.5	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Simple Asphy, SIAS

Full text of H-phrases: see section 16. This product has a variable composition that is based on the composition of the individual feedstocks, as well as the extraction location of each feedstock. The listed percentages represent expected variations in composition but are not absolute. If additional information is required, contact the Manufacturer in Section 1 of this SDS.

3.2. Mixture

Not applicable

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Give oxygen or artificial respiration if necessary. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: For brief contact with a small amount: Rewarm with body heat. Get immediate medical advice/attention. For extensive contact or a large amount: Immediately call a poison center/doctor and follow their advice. Specific treatment is urgent, incorrect first-aid practices will aggravate the injury. Protect affected area with a loose cover until proper medical treatment is received.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain immediate medical attention.

First-aid Measures After Ingestion: Ingestion is an unlikely route of exposure for a gas. Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: May cause frostbite on contact with the liquid. Asphyxia by lack of oxygen: risk of death.

Symptoms/Injuries After Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Symptoms/Injuries After Skin Contact: Contact with gas/liquid escaping the container can cause frostbite and freeze burns.

Butane-Isobutane Mix

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Eye Contact: Contact with gas/liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with gas/liquid escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Do not extinguish burning gas if flow cannot be shut off immediately. Extinguish secondary FIRES with appropriate materials.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Extremely flammable gas.

Explosion Hazard: May form flammable/explosive vapor-air mixture. Container may explode in heat of fire.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂).

Other Information: Use water spray to disperse vapors. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Eliminate every possible source of ignition. Do not get in eyes, on skin, or on clothing. Do not breathe gas.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Eliminate ignition sources first, then ventilate the area. Isolate area and remove unnecessary personnel. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Stop leak, if possible without risk. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable. Ruptured cylinders may rocket. Do not pressurize, cut, or weld containers. Asphyxiating gas at high concentrations.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Do not breathe gas.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Butane-Isobutane Mix

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep in fireproof place. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Industrial Use

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

n-Butane (106-97-8)		
USA ACGIH	ACGIH OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
USA NIOSH	NIOSH REL (TWA)	1900 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	800 ppm
USA IDLH	IDLH [ppm]	1600 ppm (>10% LEL)
Isobutane (75-28-5)		
USA ACGIH	ACGIH OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
USA NIOSH	NIOSH REL (TWA)	1900 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	800 ppm
Isopentane (78-78-4)		
USA ACGIH	ACGIH OEL TWA [ppm]	1000 ppm (Pentane, all isomers)
Propane (74-98-6)		
USA ACGIH	ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
USA NIOSH	NIOSH REL (TWA)	1800 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	1000 ppm
USA IDLH	IDLH [ppm]	2100 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) [1]	1800 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	1000 ppm
n-Pentane (109-66-0)		
USA ACGIH	ACGIH OEL TWA [ppm]	1000 ppm (Pentane, all isomers)
USA NIOSH	NIOSH REL (TWA)	350 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	120 ppm
USA NIOSH	NIOSH REL (Ceiling)	1800 mg/m ³
USA NIOSH	NIOSH REL C [ppm]	610 ppm
USA IDLH	IDLH [ppm]	1500 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) [1]	2950 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	1000 ppm
Ethane (74-84-0)		
USA ACGIH	ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content

8.2. Exposure Controls

Appropriate Engineering Controls

: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Gas detectors should be used when flammable gases or vapors may be released. Oxygen detectors should be used when asphyxiating gases may be released.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles or glasses. Face shield as required by task. Insufficient ventilation: wear respiratory protection. Respiratory protection, including supplied air, as appropriate.



Butane-Isobutane Mix

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Materials for Protective Clothing	: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.
Hand Protection	: Wear protective gloves. If material is cold, wear thermally resistant protective gloves.
Eye and Face Protection	: Chemical safety goggles or safety glasses with side shields. Faceshield as determined by task.
Skin and Body Protection	: Wear suitable protective clothing.
Respiratory Protection	: Use a NIOSH-approved self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.
Thermal Hazard Protection	: Wear thermally resistant protective clothing.
Other Information	: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Gas
Appearance	: Colorless liquefied gas
Odor	: Disagreeable
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: -138 °C (-216.4 °F)
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: -76 °C (-104.8 °F)
Auto-ignition Temperature	: 405 °C (761 °F)
Decomposition Temperature	: No data available
Flammability	: Extremely flammable gas
Vapor Pressure	: 40.5 – 44.5 psi (@ 38 °C / 100.4 °F)
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: 0.579
Solubility	: Slightly soluble in water. Soluble in hydrocarbons, alcohol, ether.
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available
Explosive Properties	: Contains gas under pressure; may explode if heated.
Lower Flammable Limit	: 1.9 %
Upper Flammable Limit	: 8.4 %

9.2. Other Information

Gas Group	: Press. Gas (Liq.)
------------------	---------------------

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Hazardous reactions will not occur under normal conditions.

10.2. Chemical Stability

Contains gas under pressure; may explode if heated.

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, open flames, sources of ignition and incompatible materials.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products

Thermal decomposition may produce: Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified. Asphyxiating gas at high concentrations.

Butane-Isobutane Mix

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

n-Butane (106-97-8)	
LC50 Inhalation Rat	30957 mg/m ³ (Exposure time: 4 h)
LC50 Inhalation Rat	276798.8 ppm
Propane (74-98-6)	
LC50 Inhalation Rat	> 800000 ppm (Exposure time: 15 min)
n-Pentane (109-66-0)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rabbit	3000 mg/kg
LC50 Inhalation Rat	364 g/m ³ (Exposure time: 4 h)
LC50 Inhalation Rat	> 20 mg/l/4h
Ethane (74-84-0)	
LC50 Inhalation Rat	> 800000 ppm/4h
Gases, petroleum, C4-rich (68477-85-0)	
LC50 Inhalation Rat	658 mg/l/4h

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Symptoms/Injuries After Skin Contact: Contact with gas/liquid escaping the container can cause frostbite and freeze burns.

Symptoms/Injuries After Eye Contact: Contact with gas/liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with gas/liquid escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Harmful to aquatic life with long lasting effects.

Isopentane (78-78-4)	
EC50 - Crustacea [1]	2.3 mg/l (Exposure time: 48 h - Species: Daphnia magna)
n-Pentane (109-66-0)	
LC50 Fish 1	9.87 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	9.74 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	11.59 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
NOEC Chronic Algae	2 mg/l

12.2. Persistence and Degradability

Butane-Isobutane Mix	
Persistence and Degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative Potential

Butane-Isobutane Mix (68477-85-0)	
Bioaccumulative Potential	Not established.
n-Butane (106-97-8)	
Partition coefficient n-octanol/water (Log Pow)	2.31 (at 20 °C (at pH 7))
Isobutane (75-28-5)	
BCF Fish 1	1.57 – 1.97
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (at 20 °C (at pH 7))

Butane-Isobutane Mix

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isopentane (78-78-4)	
Partition coefficient n-octanol/water (Log Pow)	4 (at 25 °C (at pH 6.6)
Propane (74-98-6)	
Partition coefficient n-octanol/water (Log Pow)	1.09 (at 20 °C (at pH 7)
n-Pentane (109-66-0)	
Partition coefficient n-octanol/water (Log Pow)	3.45 (at 25 °C (at pH 7)
Ethane (74-84-0)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (at 20 °C (at pH 7)
Gases, petroleum, C4-rich (68477-85-0)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8

12.4. Mobility in Soil

Butane-Isobutane Mix (68477-85-0)	
Ecology - Soil	Leaches if exposed to water.

12.5. Other Adverse Effects

Other Adverse Effects : None known.
Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Treatment Methods: Material should be recycled if possible. Incineration is also an acceptable method for disposal.

Sewage Disposal Recommendations: Do not dispose of waste into sewer.

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions. Handle empty containers with care because residual vapors are flammable. Empty gas cylinders should be returned to the vendor for recycling or refilling. Do not puncture or incinerate container.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name : PETROLEUM GASES, LIQUEFIED
Hazard Class : 2.1
Identification Number : UN1075
Label Codes : 2.1
ERG Number : 115



14.2. In Accordance with IMDG

Proper Shipping Name : PETROLEUM GASES, LIQUEFIED
Hazard Class : 2
Division : 2.1
Identification Number : UN1075
Label Codes : 2.1
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U



14.3. In Accordance with IATA

Proper Shipping Name : PETROLEUM GASES, LIQUEFIED
Identification Number : UN1075
Hazard Class : 2
Label Codes : 2.1,
Division : 2.1
ERG Code (IATA) : 10L



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Butane-Isobutane Mix (68477-85-0)
--

Butane-Isobutane Mix

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Physical hazard - Gas under pressure Health hazard - Simple asphyxiant
n-Butane (106-97-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Isobutane (75-28-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Isopentane (78-78-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Propane (74-98-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
n-Pentane (109-66-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Ethane (74-84-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Gases, petroleum, C4-rich (68477-85-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
EPA Toxic Release Inventory Information	
For more information concerning the Toxic Release Inventory concerning this product, please contact the Manufacturer as noted in Section 1 and ask for the Environmental Group. Please note that there is considerable variability in this product as noted in Section 3.	

15.2. US State Regulations

n-Butane (106-97-8)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
Isobutane (75-28-5)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
Isopentane (78-78-4)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
Propane (74-98-6)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
n-Pentane (109-66-0)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
Ethane (74-84-0)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision	: 01/10/2023
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

Butane-Isobutane Mix

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

GHS Full Text Phrases:

H220	Extremely flammable gas
H224	Extremely flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H336	May cause drowsiness or dizziness
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)