

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Substance

Product Name: Petroleum (Sour) Natural Gas Condensate

CAS-No.: 64741-47-5

Synonyms: Gas drip (sour), field liquids (sour), Petroleum field condensate (sour)

1.2. Intended Use of the Product

Use of the Substance/Mixture: Industrial Use

1.3. Name, Address, and Telephone of the Responsible Party

Corporation

ONEOK, Inc.

100 W. Fifth Street

Tulsa, OK 74103

Tel (888) 417-6275

Fax (918) 588-7543

www.oneok.com

1.4. Emergency Telephone Number

Emergency Number

: For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night within USA and Canada: 1-800-424-9300 or
+1 703-527-3887 (collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US Classification

Flammable liquids Category 1	H224
Skin corrosion/irritation Category 2	H315
Germ cell mutagenicity Category 1B	H340
Carcinogenicity Category 1A	H350
Reproductive toxicity Category 2	H361
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity (repeated exposure) Category 1	H372
Aspiration hazard Category 1	H304
Hazardous to the aquatic environment - Acute Hazard Category 2	H401
Hazardous to the aquatic environment - Chronic Hazard Category 2	H411

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)

:



GHS02



GHS07



GHS08



GHS09

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H224 - Extremely flammable liquid and vapor.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H340 - May cause genetic defects.
H350 - May cause cancer.
H361 - Suspected of damaging fertility or the unborn child.
H372 - Causes damage to organs (hematopoietic system, nervous system, hearing organs, blood) through prolonged or repeated exposure.
H401 - Toxic to aquatic life.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Petroleum (Sour) Natural Gas Condensate

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe mist, vapors, spray, fume.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P301+P310 - If swallowed: Immediately call a poison center or doctor.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P321 - Specific treatment (see section 4 on this SDS).
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.
P391 - Collect spillage.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

May displace oxygen and cause rapid suffocation. Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Name : Petroleum (Sour) Natural Gas Condensate

CAS-No. : 64741-47-5

Name	Synonyms	Product Identifier	%	GHS US classification
Natural gas condensates, petroleum	Natural gas condensates (petroleum) / Natural gas condensates, (petroleum) / Condensate / Condensates / Natural gas condensates (petroleum) - low boiling point naphtha - unspecified / Low boiling point naphtha - unspecified / Natural gas condensation products (mineral oil), low-boiling heavy gasoline / Natural gas condensate / Natural gas condensates (petroleum); Low boiling point naphtha -unspecified [A complex combination of hydrocarbons separated as a liquid from natural gas in a surface separator by retrograde condensation. It consists mainly of hydrocarbons having carbon numbers predominantly in the range of C2 to C20. It is a liquid at atmospheric temperature and pressure.]	(CAS-No.) 64741-47-5	70-99	Flam. Liq. 1, H224 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Hexane	Hexane, n- / n-Hexane / Normal hexane	(CAS-No.) 110-54-3	5-25	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Petroleum (Sour) Natural Gas Condensate

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene	Benzene, methyl- / Methylbenzene / Phenylmethane / TOLUENE	(CAS-No.) 108-88-3	1-15	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
Xylenes (o-, m-, p- isomers)	Benzene, dimethyl- / Dimethylbenzene (mixed isomers) / Xylene / Xylene (all isomers) / Xylene (mixed isomers) / Xylene (o-, m-, p- isomers) / Xylenes / Xylenes (mixed isomers) / Dimethylbenzene / XYLENE / Benzene, dimethyl-, mixed isomers / Xylol / Xylene, mixed isomers / Xylenes (meta-, ortho-, para-) / Xylene (mixture), including m-xylene, o-xylene, p-xylene / Xylene (o-,m-,p- isomer mixture) / Dimethylbenzene (2-, 3-, 4-isomers) / Dimethylbenzene (mixed 2-, 3-, 4-isomers) / C8 Disubstituted benzenes / Dimethylbenzenes / Xylene isomers mixture	(CAS-No.) 1330-20-7	1-12	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 STOT SE 3, H336 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
Benzene	Cyclohexatriene / Benzol	(CAS-No.) 71-43-2	1-2	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 1B, H340 Carc. 1A, H350 STOT SE 3, H336 STOT SE 3, H335 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
Hydrogen sulfide	Hydrogen sulfide (H2S) / Hydrogen sulphide / Sulfur hydride / Dihydrogen sulphide / hydrogen sulfide / Hydrogen sulphide, hydrogen sulfide / Sulfane	(CAS-No.) 7783-06-4	≤ 1	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Acute Tox. 2 (Inhalation:gas), H330 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT SE 1, H370 Aquatic Acute 1, H400

Full text of H-phrases: see section 16. This product has a variable composition that is based on the composition of the individual feedstocks, as well as the extraction location of each feedstock. The listed percentages represent expected variations in composition but are not absolute. If additional information is required, contact the Manufacturer in Section 1 of this SDS.

3.2. Mixture

Not applicable

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

First-aid Measures General: First aid personnel should wear appropriate protective equipment during any rescue. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists. This product contains hydrogen sulfide, which is a toxic gas that can be fatal. It also has a rotten egg smell that causes odor fatigue very quickly and shouldn't be used as an indicator for the presence of gas.

First-aid Measures After Skin Contact: Immediately remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. Wash with plenty of soap and water. If exposed or concerned: Get medical advice/attention.

Petroleum (Sour) Natural Gas Condensate

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice.

First-aid Measures After Ingestion: Turn affected person(s) on their side and maintain in that position to prevent aspiration. Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Symptoms/Injuries: May cause drowsiness and dizziness. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs (hematopoietic system, blood, nervous system, hearing organs) through prolonged or repeated exposure. Causes skin irritation. May cause genetic defects. May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death. This product contains hydrogen sulfide, which is a toxic gas that can be fatal. It also has a rotten egg smell that causes odor fatigue very quickly and shouldn't be used as an indicator for the presence of gas.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms: May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs (hematopoietic system, blood, hearing organs, nervous system) through prolonged or repeated exposure. May cause genetic defects.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Extremely flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂), Sulfur oxides.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Eliminate ignition sources first, then ventilate the area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Petroleum (Sour) Natural Gas Condensate

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable. In high concentrations, fumes may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Exposed person may not be aware of asphyxiation.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist, vapors, spray, fume. Do not get in eyes, on skin, or on clothing. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Industrial Use

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Benzene (71-43-2)		
USA ACGIH	ACGIH OEL TWA [ppm]	0.5 ppm
USA ACGIH	ACGIH OEL STEL [ppm]	2.5 ppm
USA ACGIH	ACGIH chemical category	Confirmed Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route
USA ACGIH	BEI (BLV)	25 µg/g Kreatinin Parameter: S-Phenylmercapturic acid - Medium: urine - Sampling time: end of shift (background) 500 µg/g Kreatinin Parameter: t,t-Muconic acid - Medium: urine - Sampling time: end of shift (background)
USA NIOSH	NIOSH REL TWA [ppm]	0.1 ppm
USA NIOSH	NIOSH REL STEL [ppm]	1 ppm
USA IDLH	IDLH [ppm]	500 ppm
USA OSHA	OSHA PEL (TWA) [2]	10 ppm 1 ppm
USA OSHA	OSHA PEL (STEL) [2]	5 ppm (see 29 CFR 1910.1028)
USA OSHA	OSHA PEL C [ppm]	25 ppm
USA OSHA	Acceptable Maximum Peak Above The Acceptable Ceiling Concentration For An 8-Hr Shift	50 ppm Peak (10 minutes)
USA OSHA	OSHA Action Level/Excursion Limit	0.5 ppm (Action Level, see 29 CFR 1910.1028)
Toluene (108-88-3)		
USA ACGIH	ACGIH OEL TWA [ppm]	20 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	BEI (BLV)	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift

Petroleum (Sour) Natural Gas Condensate

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		0.3 mg/g Kreatinin Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)
USA NIOSH	NIOSH REL (TWA)	375 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	100 ppm
USA NIOSH	NIOSH REL (STEL)	560 mg/m ³
USA NIOSH	NIOSH REL STEL [ppm]	150 ppm
USA IDLH	IDLH [ppm]	500 ppm
USA OSHA	OSHA PEL (TWA) [2]	200 ppm
USA OSHA	OSHA PEL C [ppm]	300 ppm
USA OSHA	Acceptable Maximum Peak Above The Acceptable Ceiling Concentration For An 8-Hr Shift	500 ppm Peak (10 minutes)
Xylenes (o-, m-, p- isomers) (1330-20-7)		
USA ACGIH	ACGIH OEL TWA [ppm]	100 ppm
USA ACGIH	ACGIH OEL STEL [ppm]	150 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA ACGIH	BEI (BLV)	1.5 g/g Kreatinin Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift
USA OSHA	OSHA PEL (TWA) [1]	435 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	100 ppm
Hexane (110-54-3)		
USA ACGIH	ACGIH OEL TWA [ppm]	50 ppm
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
USA ACGIH	BEI (BLV)	0.5 mg/l Parameter: 2,5-Hexanedione without hydrolysis - Medium: urine - Sampling time: end of shift
USA NIOSH	NIOSH REL (TWA)	180 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	50 ppm
USA IDLH	IDLH [ppm]	1100 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) [1]	1800 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	500 ppm
Hydrogen sulfide (7783-06-4)		
USA ACGIH	ACGIH OEL TWA [ppm]	1 ppm
USA ACGIH	ACGIH OEL STEL [ppm]	5 ppm
USA NIOSH	NIOSH REL (Ceiling)	15 mg/m ³
USA NIOSH	NIOSH REL C [ppm]	10 ppm
USA IDLH	IDLH [ppm]	100 ppm
USA OSHA	OSHA PEL C [ppm]	20 ppm
USA OSHA	Acceptable Maximum Peak Above The Acceptable Ceiling Concentration For An 8-Hr Shift	50 ppm Peak (10 minutes once, only if no other measurable exposure occurs)

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles or glasses. Face shield. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

Hand Protection

: Wear protective gloves.

Petroleum (Sour) Natural Gas Condensate

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Eye and Face Protection	: Chemical safety goggles or safety glasses with side shields. Faceshield as determined by task.
Skin and Body Protection	: Wear suitable protective clothing.
Respiratory Protection	: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.
Other Information	: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Clear, colorless liquid
Odor	: Gasoline odor with rotten egg
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: -5.5 – 316 °C (20 – 600 °F)
Flash Point	: -40 °C (-40 °F)
Auto-ignition Temperature	: 260 °C (500 °F)
Decomposition Temperature	: No data available
Flammability	: Not applicable
Vapor Pressure	: 14 – 600 atm (@ 38 °C / 100.4 °F)
Relative Vapor Density at 20°C	: 3.4
Relative Density	: No data available
Specific Gravity	: 0.5 – 0.75
Solubility	: Negligible in water. Soluble/miscible in hydrocarbons.
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available
Lower Flammable Limit	: 0.4 %
Upper Flammable Limit	: 11 %

9.2. Other Information

No additional information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

10.2. Chemical Stability

Extremely flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

10.3. Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

10.4. Conditions to Avoid

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products

Carbon and sulfur oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

Benzene (71-43-2)	
LD50 Oral Rat	810 mg/kg

Petroleum (Sour) Natural Gas Condensate

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

LD50 Dermal Rabbit	> 8200 mg/kg
LC50 Inhalation Rat	44.66 mg/l/4h
Toluene (108-88-3)	
LD50 Oral Rat	2600 mg/kg
LD50 Dermal Rabbit	12000 mg/kg
LC50 Inhalation Rat	25.7 mg/l/4h
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 Oral Rat	> 5000 mg/kg
ATE (Dermal)	1,100.00 mg/kg body weight
ATE (Vapors)	11.00 mg/l/4h
Hexane (110-54-3)	
LD50 Oral Rat	25 g/kg
LD50 Dermal Rabbit	3000 mg/kg
LC50 Inhalation Rat	169 mg/l/4h
LC50 Inhalation Rat	48000 ppm/4h
Natural gas condensates, petroleum (64741-47-5)	
LD50 Oral Rat	14000 mg/kg
LD50 Dermal Rabbit	> 6000 mg/kg
LC50 Inhalation Rat	> 5.2 mg/l/4h
Hydrogen sulfide (7783-06-4)	
LC50 Inhalation Rat	444 ppm/4h

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: May cause genetic defects.

Carcinogenicity: May cause cancer.

Benzene (71-43-2)	
IARC group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens, Evidence of Carcinogenicity.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.
OSHA Specifically Regulated Carcinogen List	In OSHA Specifically Regulated Carcinogen list.
Toluene (108-88-3)	
IARC group	3
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs (Hematopoietic system, nervous system, hearing organs, blood) through prolonged or repeated exposure.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death. This product contains hydrogen sulfide, which is a toxic gas that can be fatal. It also has a rotten egg smell that causes odor fatigue very quickly and shouldn't be used as an indicator for the presence of gas.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

Chronic Symptoms: May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs (hematopoietic system, blood, hearing organs, nervous system) through prolonged or repeated exposure. May cause genetic defects.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General

: Toxic to aquatic life with long lasting effects.

Petroleum (Sour) Natural Gas Condensate

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Benzene (71-43-2)	
LC50 Fish 1	10.7 – 14.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	8.76 – 15.6 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	5.3 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 - Crustacea [2]	10 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ErC50 (Algae)	29 mg/l
NOEC Chronic Fish	0.8 mg/l
Toluene (108-88-3)	
LC50 Fish 1	15.22 (15.22 – 19.05) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	5.46 (5.46 – 9.83) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 Fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC Chronic Fish	1.4 mg/l (Oncorhynchus kisutch)
NOEC Chronic Crustacea	0.74 mg/l (Ceriodaphnia dubia)
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 Fish 1	3.3 mg/l
EC50 - Crustacea [1]	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 Fish 2	2.661 (2.661 – 4.093) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
NOEC Chronic Crustacea	1.17 mg/l
Hexane (110-54-3)	
LC50 Fish 1	2.1 – 2.98 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	3.88 mg/l
Natural gas condensates, petroleum (64741-47-5)	
LC50 Fish 1	4.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
Hydrogen sulfide (7783-06-4)	
LC50 Fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC50 Fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

12.2. Persistence and Degradability

Petroleum (Sour) Natural Gas Condensate (64741-47-5)	
Persistence and Degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative Potential

Petroleum (Sour) Natural Gas Condensate (64741-47-5)	
Bioaccumulative Potential	Not established.
Benzene (71-43-2)	
BCF Fish 1	3.5 – 4.4
Partition coefficient n-octanol/water (Log Pow)	2.13
Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7))
Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF Fish 1	0.6 (0.6 – 15)
Partition coefficient n-octanol/water (Log Pow)	2.77 – 3.15
Hexane (110-54-3)	
Partition coefficient n-octanol/water (Log Pow)	4 (at 20 °C (at pH 7))
Natural gas condensates, petroleum (64741-47-5)	
Partition coefficient n-octanol/water (Log Pow)	2.2 – 6.5 (at 23 °C (at pH 6.2))
Hydrogen sulfide (7783-06-4)	
BCF Fish 1	(no bioaccumulation expected)
Partition coefficient n-octanol/water (Log Pow)	0.45 (at 25 °C)

12.4. Mobility in Soil

Petroleum (Sour) Natural Gas Condensate (64741-47-5)	
Ecology - Soil	Leaches into groundwater.

12.5. Other Adverse Effects

Other Adverse Effects : None known.

Petroleum (Sour) Natural Gas Condensate

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

Waste Treatment Methods: Material should be recycled if possible. Incineration is also an acceptable method for disposal.

Sewage Disposal Recommendations: Do not dispose of waste into sewer.

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name : HYDROCARBONS, LIQUID, N.O.S.
Hazard Class : 3
Identification Number : UN3295
Label Codes : 3
Packing Group : I or II *
Marine Pollutant : Marine pollutant
ERG Number : 128
Notes : * - Use Packing Group II for Initial Boiling Point > 35 °C (95 °F); else, use Pack Group I



14.2. In Accordance with IMDG

Proper Shipping Name : HYDROCARBONS, LIQUID, N.O.S.
Hazard Class : 3
Identification Number : UN3295
Packing Group : I or II *
Label Codes : 3
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D
Marine Pollutant : Marine pollutant
Notes : * - Use Packing Group II for Initial Boiling Point > 35 °C (95 °F); else, use Pack Group I



14.3. In Accordance with IATA

Proper Shipping Name : HYDROCARBONS, LIQUID, N.O.S.
Packing Group : I or II *
Identification Number : UN3295
Hazard Class : 3
Label Codes : 3
ERG Code (IATA) : 3H
Notes : * - Use Packing Group II for Initial Boiling Point > 35 °C (95 °F); else, use Pack Group I



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Petroleum (Sour) Natural Gas Condensate (64741-47-5)	
SARA Section 311/312 Hazard Classes	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Carcinogenicity Health hazard - Reproductive toxicity Health hazard - Skin corrosion or Irritation Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Germ cell mutagenicity Health hazard - Aspiration hazard
Benzene (71-43-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	10 lb

Petroleum (Sour) Natural Gas Condensate

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SARA Section 313 - Emission Reporting	0.1 %
Toluene (108-88-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
SARA Section 313 - Emission Reporting	1 %
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 313 - Emission Reporting	1 %
Hexane (110-54-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
SARA Section 313 - Emission Reporting	1 %
Natural gas condensates, petroleum (64741-47-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Hydrogen sulfide (7783-06-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on the United States SARA Section 302 Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb
SARA Section 313 - Emission Reporting	1 %
EPA Toxic Release Inventory Information	
For more information concerning the Toxic Release Inventory concerning this product, please contact the Manufacturer as noted in Section 1 and ask for the Environmental Group. Please note that there is considerable variability in this product as noted in Section 3.	

15.2. US State Regulations

Benzene (71-43-2)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Toluene (108-88-3)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Xylenes (o-, m-, p- isomers) (1330-20-7)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Hexane (110-54-3)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
Hydrogen sulfide (7783-06-4)
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Petroleum (Sour) Natural Gas Condensate

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

California Proposition 65



WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Benzene (71-43-2)	X	X		X
Toluene (108-88-3)		X		
Hexane (110-54-3)				X

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 01/10/2023

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

GHS Full Text Phrases:

H220	Extremely flammable gas
H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H330	Fatal if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)