

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361

GEN_SOF Number 82166

1. PRODUCT AND COMPANY IDENTIFICATION

Product information

Product name : Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Recommended use : Air Freshener

Manufacturer, importer, supplier : S.C. Johnson & Son, Inc.
1525 Howe Street
Racine WI 53403-2236

Telephone : +1 8005585252

Emergency telephone number : 24 Hour Medical Emergency Phone: (866)231-5406
24 Hour Transport Emergency Phone: (800)424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Globally Harmonized System (GHS) Classification

Hazard classification	Hazard category	Hazards identification
Aerosol	Category 1	Extremely flammable aerosol.
Eye irritation	Category 2B	Causes eye irritation.
Gases under pressure	Compressed gas	Contains gas under pressure; may explode if heated.

Labelling

Hazard symbols

Flame
Gas cylinder

Signal word

Danger

Hazard statements

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes eye irritation.

Precautionary statements

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361

GEN_SOF Number 82166

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/ attention.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Protect from sunlight. Store in a well-ventilated place.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

Other hazards : Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.
Excessive exposure to spray mist, fog or vapour may cause respiratory irritation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No.	Weight percent
Acetone	67-64-1	30.00 - 60.00
Isobutane	75-28-5	10.00 - 30.00
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-47-8	10.00 - 30.00
Propane	74-98-6	1.00 - 5.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

4. FIRST AID MEASURES

Eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Skin contact : No special requirements

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361

GEN_SOF Number 82166

Inhalation : No special requirements.

Ingestion : No special requirements

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Specific hazards during firefighting : Aerosol Product - Containers may rocket or explode in heat of fire.

Further information : Fight fire from maximum distance or protected area. Cool and use caution when approaching or handling fire-exposed containers. Wear full protective clothing and positive pressure self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Remove all sources of ignition.
Wash thoroughly after handling.

Environmental precautions : Outside of normal use, avoid release to the environment.

Methods and materials for containment and cleaning up : If damage occurs to aerosol can:
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Use only non-sparking equipment.
Dike large spills.
Clean residue from spill site.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361

GEN_SOF Number 82166

7. HANDLING AND STORAGE

Handling

Precautions for safe handling

: Avoid contact with skin, eyes and clothing.
For personal protection see section 8.
Note: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. For more information visit www.inhalant.org.
Use only as directed.
KEEP OUT OF REACH OF CHILDREN AND PETS.
Pressurized container.
Do not pierce or burn, even after use.
Wash thoroughly after handling.

Advice on protection against fire and explosion

: Keep away from sources of ignition - No smoking.
Do not spray on an open flame or other ignition source.

Storage

Requirements for storage areas and containers

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Keep in a dry, cool and well-ventilated place.
Protect from sunlight.
Store in a well-ventilated place.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361
GEN_SOF Number 82166

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Components	CAS-No.	mg/m3	ppm	Non-standard units	Basis
Acetone	67-64-1	-	500 ppm	-	ACGIH STEL
Acetone	67-64-1	-	250 ppm	-	ACGIH TWA
Acetone	67-64-1	2,400 mg/m3	1,000 ppm	-	OSHA TWA
Isobutane	75-28-5	-	1,000 ppm	-	ACGIH STEL
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-47-8	1,200 mg/m3	152 ppm	-	SUPPLIER
Propane	74-98-6	-	-	-	ACGIH TWA
Propane	74-98-6	1,800 mg/m3	1,000 ppm	-	OSHA TWA

Personal protective equipment

Respiratory protection : No special requirements.

Hand protection : No special requirements.

Eye protection : No special requirements.

Skin and body protection : No special requirements.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361
GEN_SOF Number 82166

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : aerosol

Color : colourless

Odor : sweet

Odour Threshold : Test not applicable for this product type

pH : Test not applicable for this product type

Melting point/freezing point : Test not applicable for this product type

Initial boiling point and boiling range : Test not applicable for this product type

Flash point : -7 °C
19.4 °F
Propellant
100 °C
212 °F
Method: Tag Closed Cup (TCC)
liquid

Evaporation rate : Test not applicable for this product type

Flammability (solid, gas) : Sustains combustion

Upper/lower flammability or explosive limits : Test not applicable for this product type

Vapour pressure : Test not applicable for this product type

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361

GEN_SOF Number 82166

Vapour density	:	
Relative density	:	0.731 g/cm3 at 20 °Cestimated
Solubility(ies)	:	partly miscible
Partition coefficient: n-octanol/water	:	Test not applicable for this product type
Auto-ignition temperature	:	not auto-flammable not auto-flammable
Decomposition temperature	:	Test not applicable for this product type
Viscosity, dynamic	:	Test not applicable for this product type
Viscosity, kinematic	:	Test not applicable for this product type
Oxidizing properties	:	
Volatile Organic Compounds Total VOC (wt. %)*	:	29.4 % - additional exemptions may apply *as defined by US Federal and State Consumer Product Regulations
Other information	:	None identified

10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under recommended storage conditions.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361
GEN_SOF Number 82166

Possibility of hazardous reactions : Stable under recommended storage conditions.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Thermal decomposition can lead to release of irritating gases and vapours.

11. TOXICOLOGICAL INFORMATION

Emergency Overview : Danger

Acute oral toxicity : LD50 2904 mg/kg

Acute inhalation toxicity : LC50 > 10 mg/L

Acute dermal toxicity : LD50 > 5000 mg/kg

GHS Properties	Classification	Routes of entry
Acute toxicity	No classification proposed	Oral
Acute toxicity	No classification proposed	Dermal
Acute toxicity	No classification proposed	Inhalation - Dust and Mist
Acute toxicity	No classification proposed	Inhalation - Vapour
Acute toxicity	No classification proposed	Inhalation - Gas
Skin corrosion/irritation	No classification proposed	-
Eye irritation	Category 2B	-

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361
GEN_SOF Number 82166

Skin sensitisation	No classification proposed	-
Respiratory sensitisation	No classification proposed	-
Germ cell mutagenicity	No classification proposed	-
Carcinogenicity	No classification proposed	-
Reproductive toxicity	No classification proposed	-
Specific target organ toxicity - single exposure	No classification proposed	-
Specific target organ toxicity - repeated exposure	No classification proposed	-
Aspiration hazard	No classification proposed	-

Aggravated Medical Condition : None known.

12. ECOLOGICAL INFORMATION

Product : The product itself has not been tested.

Toxicity

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

Toxicity to fish

Components	End point	Species	Value	Exposure time
Acetone	static test LC50	Oncorhynchus mykiss (rainbow trout)	6,210 mg/l	96 h
Isobutane	LC50 QSAR	Fish	27.98 mg/l	96 h

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200

**Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US**

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361

GEN_SOF Number 82166

Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	LC50	Fish	> 1,028 mg/l	96 h
Propane	LC50 QSAR	Fish	49.9 mg/l	96 h

Toxicity to aquatic invertebrates

Components	End point	Species	Value	Exposure time
Acetone	static test LC50	Daphnia pulex (Water flea)	8,800 mg/l	48 h
	NOEC	Daphnia magna	2,212 mg/l	28 d
Isobutane	LC50 QSAR	Daphnid	16.33 mg/l	48 h
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC50	Daphnid	> 3,193 mg/l	48 h
Propane	LC50	Daphnid	27.14 mg/l	48 h

Toxicity to aquatic plants

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200

**Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US**

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361

GEN_SOF Number 82166

Components	End point	Species	Value	Exposure time
Acetone	NOEC	Microcystis aeruginosa (blue-green algae)	530 mg/l	8 d
Isobutane	EC50 QSAR	Green algae	8.57 mg/l	96 h
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC50	Skeletonema costatum	> 3,198 mg/l	72 h
Propane	EC50	Green algae	11.89 mg/l	96 h

Persistence and degradability

Component	Biodegradation	Exposure time	Summary
Acetone	90.9 %	28 d	Readily biodegradable.
Isobutane	70 %	< 10 d	Readily biodegradable.
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	74 %	28 d	Readily biodegradable.
Propane	70 %	< 10 d	Readily biodegradable.

Bioaccumulative potential

Component	Bioconcentration factor (BCF)	Partition Coefficient n-Octanol/water (log)
Acetone	0.69	-0.23
Isobutane	1.57 - 1.97	2.8
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	61 - 159	No data available
Propane	13	2.36

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361

GEN_SOF Number 82166

Mobility

Component	End point	Value
Acetone	No data available	
Isobutane	No data available	
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	No data available	
Propane	Koc	460

PBT and vPvB assessment

Component	Results
Acetone	Not fulfilling PBT and vPvB criteria
Isobutane	Not fulfilling PBT and vPvB criteria
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not fulfilling PBT and vPvB criteria
Propane	Not fulfilling PBT and vPvB criteria

Other adverse effects : None known.

13. DISPOSAL CONSIDERATIONS

Consumer may discard empty container in trash, or recycle where facilities exist.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361

GEN_SOF Number 82166

	Land transport	Sea transport	Air transport
UN number or identification number	1950	1950	1950
UN proper shipping name	AEROSOLS, flammable	AEROSOLS, flammable	AEROSOLS, flammable
Transport hazard class(es)	2.1	2	2.1
Packing group	-	-	-
Environmental hazards	-	-	-
Special precautions for user	Limited quantities derogation may be applicable to this product, please check transport documents.	Limited quantities derogation may be applicable to this product, please check transport documents.	Limited quantities derogation may be applicable to this product, please check transport documents.

15. REGULATORY INFORMATION

Notification status : All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

California Prop. 65 : This product is not subject to the reporting requirements under California's Proposition 65.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



Gld LgAuto Van Crml KTO Rfl 6.2OZ/6 US

Version 1.1

Print Date 10/23/2025

Revision Date 03/24/2025

SDS Number 350000046361

GEN_SOF Number 82166

16. OTHER INFORMATION

HMIS Ratings

Health	1
Flammability	4
Reactivity	4

NFPA Ratings

Health	1
Fire	4
Reactivity	0
Special	-

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use.

Further information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by	SC Johnson Global Safety Assessment & Regulatory Affairs (GSARA)
-------------	--