

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

1. PRODUCT AND COMPANY IDENTIFICATION

Product information

Product name : GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Recommended use : Air Freshener

Manufacturer, importer, supplier : S.C. Johnson & Son, Inc.
1525 Howe Street
Racine WI 53403-2236

Telephone : +1 8005585252
Emergency telephone number : 24 Hour Medical Emergency Phone: (866)231-5406
24 Hour Transport Emergency Phone: (800)424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Globally Harmonized System (GHS) Classification

Hazard classification	Hazard category	Hazards identification
Flammable liquids	Category 4	Combustible liquid.
Eye irritation	Category 2B	Causes eye irritation.

Labelling

Signal word

Warning

Hazard statements

Combustible liquid.
Causes eye irritation.

Precautionary statements

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
In case of fire: Use alcohol-resistant foam, carbon dioxide or dry sand to extinguish.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

Store in a well-ventilated place. Keep cool.
Dispose of contents/ container to an approved incineration plant.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Wear protective gloves.
Wash hands thoroughly after handling.
Other hazards : None identified

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS-No.	Weight percent
Benzyl Acetate	140-11-4	5.00 - 10.00
Fragrance - Trade Secret	Mixture	60.00 - 100.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

4. FIRST AID MEASURES

Eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Skin contact : Wash off with plenty of water. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice/ attention.

Inhalation : No special requirements.

Ingestion : No special requirements

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

Specific hazards during firefighting : Flammable liquid. Vapors are heavier than air and may travel to a source of ignition and flash back. Liquid run-off to sewers may create fire/explosion hazard. Do not use a solid water stream as it may scatter and spread fire. Container may melt and leak in heat of fire.

Further information : Cool and use caution when approaching or handling fire-exposed containers. For large quantities of flammable liquids, consider containment to prevent the spread of fire. Wear full protective clothing and positive pressure self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Remove all sources of ignition.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Wear personal protective equipment.
Wash thoroughly after handling.

Environmental precautions : Outside of normal use, avoid release to the environment.

Methods and materials for containment and cleaning up : Use only non-sparking equipment.
Dike large spills.
Clean residue from spill site.

7. HANDLING AND STORAGE

Handling

Precautions for safe handling : Avoid contact with skin, eyes and clothing.
For personal protection see section 8.
Use only as directed.
KEEP OUT OF REACH OF CHILDREN AND PETS.
Contaminated work clothing should not be allowed out of the workplace.
Avoid breathing vapours, mist or gas.
Wash thoroughly after handling.

Advice on protection : Keep away from sources of ignition - No smoking.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

against fire and explosion

Storage

Requirements for storage areas and containers : Keep container closed when not in use.
Store in a well-ventilated place. Keep cool.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Components	CAS-No.	mg/m3	ppm	Non-standard units	Basis
Benzyl Acetate	140-11-4	-	10 ppm	-	ACGIH TWA

Occupational Exposure Limits

Components	CAS-No.	mg/m3	ppm	Non-standard units	Basis
Benzyl Acetate	140-11-4	-	10 ppm	-	ACGIH TWA

Personal protective equipment

Respiratory protection : Substantial amounts of mist/vapors can be controlled with local exhaust ventilation or respiratory protection.

Hand protection : Wear suitable gloves.

Eye protection : Safety glasses with side-shields

Skin and body protection : No special requirements.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

Form	: liquid
Color	: light yellow to yellow
Odor	: Marine/Ozone
Odour Threshold	: Test not applicable for this product type
pH	: Mixture is non-polar
Melting point/freezing point	: <-20°C
Initial boiling point and boiling range	: 70 - 140 °C
Flash point	: 83 °C 181.4 °F Method: ASTM D 93
Evaporation rate	: Test not applicable for this product type
Flammability (solid, gas)	: Sustains combustion
Upper/lower flammability or explosive limits	: Not determined as it does not affect the liquid flammability classification. Flash point is used for classification of flammable liquids.
Vapour pressure	: 0.15 hPa at 20 °C
Vapour density	: > 1
Relative density	: 0.975 g/cm3 at 25 °C

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

Solubility(ies)	: immiscible	
Partition coefficient: n-octanol/water	: Not required as the product is a mixture.	
Auto-ignition temperature	: not auto-flammable	
Decomposition temperature	: Not measured as mixture is not self-reactive	
Viscosity, dynamic	: Test not applicable for this product type	
Viscosity, kinematic	: similar to water	
Oxidizing properties	: Not required	
Volatile Organic Compounds Total VOC (wt. %)*	: 72 % - additional exemptions may apply *as defined by US Federal and State Consumer Product Regulations	
Other information	: None identified	:

10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	:
Possibility of hazardous reactions	: Stable under recommended storage conditions.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : Thermal decomposition can lead to release of irritating gases and vapours.

11. TOXICOLOGICAL INFORMATION

Emergency Overview : Warning

Acute oral toxicity : LD50 > 5000 mg/kg

Acute inhalation toxicity : LC50 > 10 mg/L

Acute dermal toxicity : LD50 > 5000 mg/kg

GHS Properties	Classification	Routes of entry
Acute toxicity	No classification proposed	Oral
Acute toxicity	No classification proposed	Dermal
Acute toxicity	No classification proposed	Inhalation - Dust and Mist
Acute toxicity	No classification proposed	Inhalation - Vapour
Acute toxicity	No classification proposed	Inhalation - Gas
Skin irritation	No classification proposed	-
Eye irritation	Category 2B	-
Skin sensitisation	No classification proposed	-
Respiratory sensitisation	No classification proposed	-
Germ cell mutagenicity	No classification proposed	-

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

Carcinogenicity	No classification proposed	-
Reproductive toxicity	No classification proposed	-
Specific target organ toxicity - single exposure	No classification proposed	-
Specific target organ toxicity - repeated exposure	No classification proposed	-
Aspiration hazard	No classification proposed	-

Aggravated Medical Condition : None known.

12. ECOLOGICAL INFORMATION

Product : The product itself has not been tested.

Toxicity

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

Toxicity to fish

Components	End point	Species	Value	Exposure time
Benzyl Acetate	flow-through test LC50	Oryzias latipes	4 mg/l	96 h
	flow-through test NOEC	Oryzias latipes	0.92 mg/l	28 d
Fragrance - Trade Secret	No data available			
Benzyl Acetate	flow-	Oryzias latipes	4 mg/l	96 h

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200

**GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS**

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

	through test LC50 flow- through test NOEC	Oryzias latipes	0.92 mg/l	28 d
2,6-dimethyloct-7-en-2-ol	static test LC50 Read- across (Analogy)	Oncorhynchus mykiss (rainbow trout)	27.8 mg/l	96 h
Cyclamen Aldehyde	LC50 QSAR	Fish	1.092 mg/l	96 h
Ethyl-2,2- dimethylhydrocinnamal	static test LC50 Read- across (Analogy) OECD Test Guideline 203	Danio rerio (zebra fish)	9 mg/l	96 h

Toxicity to aquatic invertebrates

Components	End point	Species	Value	Exposure time
Benzyl Acetate	semi- static test EC50	Daphnia magna (Water flea)	17 mg/l	48 h
Fragrance - Trade Secret	No data			

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200

**GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS**

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

	available			
Benzyl Acetate	semi-static test EC50	Daphnia magna (Water flea)	17 mg/l	48 h
2,6-dimethyloct-7-en-2-ol	static test EC50	Daphnia magna (Water flea)	38 mg/l	48 h
	NOEC Read-across (Analogy)	Daphnia magna	9.5 mg/l	21 d
Cyclamen Aldehyde	semi-static test EC50	Daphnia magna (Water flea)	1.4 mg/l	48 h
Ethyl-2,2-dimethylhydrocinnamal	semi-static test EC50 Read-across (Analogy) OECD Test Guideline 202	Daphnia magna (Water flea)	1.8 mg/l	48 h

Toxicity to aquatic plants

Components	End point	Species	Value	Exposure time
Benzyl Acetate	static test EC50	Desmodesmus subspicatus (green algae)	110 mg/l	72 h

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200

**GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS**

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

Fragrance - Trade Secret	No data available			
Benzyl Acetate	static test EC50	Desmodesmus subspicatus (green algae)	110 mg/l	72 h
2,6-dimethyloct-7-en-2-ol	static test EC50	Desmodesmus subspicatus (green algae)	80 mg/l	72 h
Cyclamen Aldehyde	static test EC50	Pseudokirchneriella subcapitata (green algae)	4.3 mg/l	72 h
Ethyl-2,2-dimethylhydrocinnamal	NOEC Measured OECD Test Guideline 201	Pseudokirchneriella subcapitata (green algae)	1.2 mg/l	72 h

Persistence and degradability

Component	Biodegradation	Exposure time	Summary
Benzyl Acetate	100 %	28 d	Readily biodegradable.
Fragrance - Trade Secret	No data available		
Benzyl Acetate	100 %	28 d	Readily biodegradable.
2,6-dimethyloct-7-en-2-ol	72 %	28 d	Readily biodegradable.
Cyclamen Aldehyde	65.5 %	28 d	Readily biodegradable.
Ethyl-2,2-dimethylhydrocinnamal	0 %	28 d	Not readily biodegradable.

Bioaccumulative potential

Component	Bioconcentration factor (BCF)	Partition Coefficient n-Octanol/water (log)
Benzyl Acetate	8 Calculated	1.96
Fragrance - Trade Secret	No data available	No data available

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

Benzyl Acetate	8 Calculated	1.96
2,6-dimethyloct-7-en-2-ol	64.8 QSAR	3
Cyclamen Aldehyde	155 QSAR	4.0
Ethyl-2,2-dimethylhydrocinnamal	186	3.9

Mobility

Component	End point	Value
Benzyl Acetate	Koc	250 estimated -
Fragrance - Trade Secret	No data available	
Benzyl Acetate	Koc	250 estimated -
2,6-dimethyloct-7-en-2-ol	log Koc	2.25 -
Cyclamen Aldehyde	log Koc	3.05 -
Ethyl-2,2-dimethylhydrocinnamal	log Koc	2.94 - 3.08

PBT and vPvB assessment

Component	Results
Benzyl Acetate	Not fulfilling PBT and vPvB criteria
Fragrance - Trade Secret	Not fulfilling PBT and vPvB criteria
Benzyl Acetate	Not fulfilling PBT and vPvB criteria
2,6-dimethyloct-7-en-2-ol	Not fulfilling PBT and vPvB criteria
Cyclamen Aldehyde	Not fulfilling PBT and vPvB criteria
Ethyl-2,2-dimethylhydrocinnamal	Not fulfilling PBT and vPvB criteria

Other adverse effects : None known.

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

13. DISPOSAL CONSIDERATIONS

Consumer may discard empty container in trash, or recycle where facilities exist.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

Land transport

Not classified as dangerous in the meaning of transport regulations.

Sea transport

Not classified as dangerous in the meaning of transport regulations.

Air transport

Not classified as dangerous in the meaning of transport regulations.

15. REGULATORY INFORMATION

Notification status : All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

California Prop. 65 : This product is not subject to the reporting requirements under California's Proposition 65.

State Right To Know

No components are subject to the Massachusetts Right to Know Act.		
No components are subject to the Massachusetts Right to Know Act.		
Minnesota HSL	Benzyl Acetate	140-11-4
	Benzyl Acetate	140-11-4
New Jersey HRTK	Benzyl Acetate	140-11-4
	Benzyl Acetate	140-11-4
Pennsylvania RTKL		
	Benzyl Acetate	140-11-4
	4-Tert-butylcyclohexyl acetate	32210-23-4

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

	2,6-dimethyloct-7-en-2-ol	18479-58-8
	Linalyl acetate	115-95-7
	2-TERT-BUTYLCYCLOHEXYL ACETATE	88-41-5
	N-Butyl acetate	123-86-4
	Benzyl Acetate	140-11-4
	4-Tert-butylcyclohexyl acetate	32210-23-4
	2,6-dimethyloct-7-en-2-ol	18479-58-8
	Linalyl acetate	115-95-7
	2-TERT-BUTYLCYCLOHEXYL ACETATE	88-41-5
	N-Butyl acetate	123-86-4

16. OTHER INFORMATION

HMIS Ratings

Health	1
Flammability	1
Reactivity	0

NFPA Ratings

Health	1
Fire	1
Reactivity	0
Special	-

This information is being provided in accordance with the Occupational Safety and Health Administration (OSHA) regulation (29 CFR 1910.1200). The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use.

Further information

Safety Data Sheet

according to Hazard Communication Standard; 29 CFR 1910.1200



GLADE® PLUG-IN® SCENTED OIL - CLEAN LINEN 2 REFILLS

Version 2.0

Print Date 10/23/2025

Revision Date 02/20/2025

SDS Number 350000037948

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by	SC Johnson Global Safety Assessment & Regulatory Affairs (GSARA)
-------------	--